
ER1A-FS/ER2A-FS 09/20/23 Item # 13563

W x D x H 27" x 29.63" x 81.63" (including 4" casters)

W x D x H 54.38" x 29.63" x 81.63" (including 4" casters)













Interior Storage Capacity (CF) (AHAM)







One Section

ER1A-FS 17.8 ft³

27" x 29.63"



Two Section

ER2A-FS

38.61 ft3

54.38" x 29.63"

п	imo	nein	ne	C	anar	itv

Overall Width x Depth

Height (including 4" casters)	81.63"	81.63"
Door Opening (W x H)	22.25" x 52.1"	22.9" x 52.1"
Depth with Door Open at 90°	55.38"	55.38"
Adjustable Shelves	3	6
Shelf Dimensions (W x D)	21.5" x 23.1"	24.3" x 21.7"
Crated Shipping Weight	279 lbs	523 lbs
Crated Length x Depth x Height	31.5" x 28.75" x 84"	58" x 31.5" x 84"
Electrical / Refrigeration	One Section ER1A-FS	Two Section ER2A-FS
Voltage	115/60/1	115/60/1
HACR Breaker	15.0 Amps	15.0 Amps
Electrical Connection (NEMA)	5-15P 🚯	5-15P 🕦
Voltage Range	103-127	103-127
Ambient Temp. Range	45° to 100°F	45° to 100°F
Control Setpoint Range	33° to 39°F	33° to 39°F
Amperage	2	4.3
Energy Consumption (kWh/day) @ASHRAE	1.06	2.1
Appox. Nominal Compres. BTU/HR (HP)	1960(1/5HP)	4291(1/3HP)
Refrigerant / Charge Amount (oz.)	R290 / (2.3oz)	R290 / (3.7oz)

Options

Additional epoxy shelves

HS-5511(1 section)

☐ HS-5512 (2 section)


Warranty


* 2 Year - Parts and Labor on entire machine. 5 Year - Parts on Compressor Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

Features

- · Energy efficient interior LED light
- Environmentally friendly R290 hydrocarbon refrigerant
- Solid state digital controller with temperature alarms and LED display (Fahrenheit or Celsius)
- Self-closing door(s) is field reversible
- Stainless steel exterior door(s) come standard with lock(s)
- Stainless steel interior floor with aluminum sides, rear, and top
- · Factory-installed casters
- · Time initiated automatic defrost
- Energy efficient heated condensate removal
- Heavy duty grey epoxy coated shelves are adjustable in 1/2" increments; 3 per section. 105 lbs. capacity
- Aluminum shelf supports
- Standard with 4" casters (two with brakes)
- 9 ft. cord and plug
- · Container Qty:

ER1A-FS: 47 ER2A-FS: 28 FRONT VIEW SIDE VIEW





PLAN VIEW

