

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Straight Front Bakery Cases

Display Cases European Straight Front Cases - Dry Cases

Model: TCGB-36UF-DR-S



___ FEATURES & BENEFITS =__

- Attractive, elegant, glass sided Euro design Straight tempered front glass and minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.
- LED interior lighting under each shelf
- High-density polyurethane insulation The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.
- Low-E coated double pane glass is tempered for safety
- Adjustable, tempered glass shelves with stainless steel front and back edges
- Stainless steel floor
- Sliding rear doors for product loading & unloading



Model	CU./FT.	# of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D x H* (inches)
TCGB-36UF-DR-S	11.8	2	-	0.4	465	361/2 x 331/8 x 501/8

Ver 20230214 Printed in U.S.A. * Height does not include 5/8" for bolt height.

(unit: inch)

Straight Front Bakery Cases

Model: TCGB-36UF-DR-S

ELECTRICAL DATA			
Voltage	115/60/1		
Plug Type	NEMA 5-15P		
Full Load Amperes	0.4		
Compressor HP	-		
Cord Length (ft.)	47/8		
Refrigerant	-		
DIMENSIONAL DATA			
Net Capacity (cu. ft.)	11.8		
Ext. Length Overall (in.)	361/2 (927mm)		
Ext. Depth Overall (in.)	331/8 (841mm)		
Ext. Height Overall (in.)*	501/8 (1272mm)		
Int. Length Overall (in.)	331/4 (846mm)		
Int. Depth Overall (in.)	21 _{1/2} (546mm)		
Int. Height Overall (in.)	25 _{5/8} (650mm)		
Shelf Size (L x D) (in.)	323/8 x 163/4		
	323/8 x 183/4		
# of Shelves	2		
Net Weight (lbs.)	353		
Gross Weight (lbs.)	465		

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 2 Year Parts and Labor Warranty


STANDARD FEATURES

• Bolt height adjustable up to 23/4"


OPTIONAL ACCESSORIES

- 1.6" caster: CAS16WBT00 (non-brake)
- 4" caster, ½" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- 6" leveling seismic leg (½", 13 TPI): 30221M0700


PLAN VIEW



TOP VIEW



FRONT VIEW



Ver.20230214



■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









^{*} Height does not include 5/8" for bolt height.