

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project:          |        |      |
|-------------------|--------|------|
| Model #:          |        |      |
| Item #:           |        |      |
| Available W/H:    |        | Qty: |
| Approval:         |        |      |
| AIA#:             | SIS #: |      |
| CSI Section 11400 |        |      |
|                   |        |      |

# Vertical Open Display Cases

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

## Model : TOM-72DXB-N TOM-72DXB-SP(-A)-N

Glass or Solid Side Panel

Extra Deep



W/ Security cover (optional)



TOM-72DXB-N

TOM-72DXB-SP-N

### $\equiv$ FEATURES & BENEFITS =

#### Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### Modern design

By integrating great contours with durable structures, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. Safety reinforced tempered glass front shield and side walls optimize the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages. Its elegant contemporary euro design will enhance any store application.

#### LED interior lighting under each shelf

- Designed to enhance impulsive sales Ideal for eye-catching displays and convenient access with fast service in high traffic area.
- Standard back-guard improves airflow
- Energy saving night curtain standard
- Optional security cover available
- Foamed with polyurethane, high-density cell insulation (CFC free)
- Perforated interior back wall and top for improved airflow
- Front air intake and rear air discharge
- Solid side panel with stainless steel interior (SP-N) or black coated interior (SP-A-N) option (lead time applies)

|                                   |         |                 |         |      | NATURAL<br>Refrigerant  | Intertek                                |
|-----------------------------------|---------|-----------------|---------|------|-------------------------|---|
| Model                             | CU./FT. | # of<br>Shelves | HP      | AMPS | Crated<br>Weight (lbs.) | $L \ge D^* \ge H^{\dagger}$<br>(inches) |
| TOM-72DXB-N<br>TOM-72DXB-SP(-A)-N | 34.1    | 8               | 3/4 x 2 | 18   | 1064                    | 683/4 x 331/4 x 783/8                   |

Ver 20220302 Printed in U.S.A.


\* Depth does not include 1-5/8" for safety bar and 1-1/8" for rear spacers. † Height does not include 5/8" for bolt height.


## Vertical Open Display Cases

#### Extra Deep Glass or Solid Side Panel

## **PLAN VIEW**

(unit : inch)





#### SIDE VIEW

**Turbo Air** : 800-627-0032

**GK**: 800-500-3519

Model : TOM-72DXB-N TOM-72DXB-SP(-A)-N

| ELECTRICAL DATA                        |                       |  |  |  |
|--|-----------------------|--|--|--|
| Voltage                                | 220/60/1              |  |  |  |
| Plug Type                              | •••• NEMA 6-20P       |  |  |  |
| Full Load Amperes                      | 18                    |  |  |  |
| Compressor HP                          | 3/4 x 4               |  |  |  |
| Cord Length (ft.)                      | 97/8                  |  |  |  |
| Refrigerant                            | R-290                 |  |  |  |
| DIMENSIONAL DATA                       |                       |  |  |  |
| Net Capacity (cu. ft.)                 | 34.1                  |  |  |  |
| Ext. Dimension (L x $D^*x H^+$ ) (in.) | 683/4 x 331/4 x 783/8 |  |  |  |
| Int. Dimension (L x D x H) (in.)       | 663/8 x 211/4 x 483/4 |  |  |  |
| # of Shelves                           | 8                     |  |  |  |
| Shelf Size (L x D) (in.)               | 331/8 x 16            |  |  |  |
| Net Weight (lbs.)                      | 890                   |  |  |  |
| Gross Weight (lbs.)                    | 1064                  |  |  |  |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. \* Depth does not include 1-5/8" for safety bar and 1-1/8" for rear spacers.

† Height does not include 5/8" for bolt height.

### WARRANTY : 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

#### STANDARD FEATURES

- Simple plug-in installation
- · Patented self-contained system, no plumbing required
- Solar powered digital thermometer
- Digital electronic thermostat with defrost control
- Bolt height adjustable up to 2<sup>3</sup>/<sub>4</sub>"
- Standard color comes in black only

#### Recommended operating conditions

TOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product. When used as a built-in, required clearance for the rear is 4" and the top is 5".

#### OPTIONAL ACCESSORIES

- 1.6" caster: CAS16WBT00 (non-brake)
- 4" caster, 1/2" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- 6" leveling seismic leg (1/2", 13 TPI): 30221M0700
- Security cover: SC-72-DXB, SCM-72-DXB, SCS-72-DX
- Price tag channel: P36DX000ZK (33"L)

Ver 20220302



(GERMAN **lurbo air** 

KNIFE

#### IRadiance Turbo air

Continued product development may necessitate specification changes without notice.

**Warranty** : 800-381-7770 **AC** : 888-900-1002

Texaking