



FROM THE
MAKERS OF



ARMORTECH



TRUE CENTER VISION

SUPPLIES CIRCULAR SIGHT PICTURE EVEN
WHEN VIEWED SLIGHTLY OFF CENTER



ARMOR FIBER TECHNOLOGY

NO EXPOSED FIBERS!



ADJUSTABLE 2ND / 3RD AXIS

THE REAL #1

ANYONE CAN CLAIM IT. WE PROVE IT!

TOOL-LESS MICRO-ADJUST WINDAGE & ELEVATION KNOBS
20 CLICKS PER REVOLUTION ADJUSTABILITY (.00156" PER CLICK)



INTERCHANGEABLE RH/LH
SIMPLY MOVE LEVEL TO TOP OF SCOPE
USING SCREW FOR LEFT HAND USE

SIGHT PIN PIVOT LOCK
ENGINEERED TO NOT VIBRATE LOOSE

INDIVIDUAL MICRO-PIN ADJUSTMENT
LOOSEN SCREWS IN PINS THEN TURN MICRO-ADJUSTMENT KNOB
TO MOVE INDIVIDUAL SIGHT PIN UP OR DOWN

PIN / FIBER OPTIONS

SIGHT PIN OPTIONS 4 PIN | 5 PIN | 7 PIN

FIBER SIZE OPTIONS .010" | .019" | .029"



follow us



We Make Archery Better!

WWW.AXCELSIGHTS.COM

ARMORTECH & ARMORTECH-HD

TOOL-LESS WINDAGE & ELEVATION THUMB LOCKS (A)

ALWAYS LOOSEN BEFORE ADJUSTING KNOB (B) & (C). RETIGHTEN AFTER MAKING ADJUSTMENTS.

MATHEWS® HARMONIC DAMPER (INCLUDED ON ARMORTECH-HD MODEL ONLY)

3-POSITION BOW MOUNTING HOLES

VIEW 1

LIGHT MOUNTING HOLE 3/8"-32 THREAD

INDIVIDUAL MICRO-PIN ADJUSTMENT

TO MOVE SINGLE SIGHT PIN OR MORE THAN ONE PIN AT THE SAME TIME, USE SUPPLIED HEX WRENCH TO LOOSEN DESIRED SIGHT PIN SCREWS 2-TURNS COUNTERCLOCKWISE. TURN MICRO-ADJUST KNOB (D) TO MOVE DESIRED SIGHT PIN/PINS UP OR DOWN. RE-TIGHTEN SIGHT PIN SCREWS HOLDING SHORT END OF SUPPLIED HX WRENCH.

WARNING: DO NOT OVERTIGHTEN SIGHT PINS!

LEGAL

ITEMS IN THIS PACKAGING ARE PATENT PENDING OR COVERED BY US PATENTS & REGISTERED TRADEMARKS.

VISIT WWW.AXCELSIGHTS.COM/LEGAL_HTML FOR A FULL LIST OF PATENTS & TRADEMARKS.

INTERCHANGEABLE RH/LH SIMPLY MOVE LEVEL TO TOP OF SCOPE USING SCREW (F) FOR LH USE.

ELEVATION KNOB (B) AND WINDAGE KNOB (C) HAVE 20 CLICKS-PER-REVOLUTION ADJUSTABILITY (.00156 PER CLICK)

WARNING: TO AVOID OVERTIGHTENING SIGHT PINS, HOLD SHORT END OF WRENCH

VIEW 2

TO GAIN MORE WINDAGE & ELEVATION

REMOVE SCREWS (E) AND LOCATE ALIGNMENT HOLES TO PROVIDE MORE OR LESS WINDAGE & ELEVATION TRAVEL.

MICRO-ADJUSTMENT KNOB FOR INDIVIDUAL SIGHT PINS

LIGHT MOUNTING HOLE 3/8"-32 THREAD

Level bowstring to vertical position and adjust scope bubble vial to level using screws (E)

To ADJUST 3RD AXIS

Bow should be canted 45° downward in bow vise. Adjust scope bubble vial to level using screw (F)

TRUE CENTER VISION

T.C.V. IS PROVIDED DUE TO THE "HOUR-GLASS" OR "VENTURI" SHAPE INSIDE SCOPE WHICH SUPPLIES A CIRCULAR SIGHT PICTURE REFERENCE EVEN WHEN VIEWED SLIGHTLY OFF-CENTER.



TUBE SHAPE SCOPES SUPPLY AN ELIPSE WHEN VIEWED OFF CENTER.
-NOT GOOD-

COMPATIBLE FOR USE WITH OPTIONAL CLASSIC MAGNUM SCOPE LENS.



ARMOR FIBER TECHNOLOGY PROVIDES 100% PROTECTION TO FIBERS THAT ARE FULLY ENCLOSED INSIDE TUBING.

NO EXPOSED FIBERS!



WARNING: This product can expose you to chemicals including Nickel Acetate, which is known to the State of California to cause cancer or birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.

LIMITED LIFETIME WARRANTY

THIS AXCEL SIGHT IS GUARANTEED ONLY TO THE ORIGINAL OWNER, WITH A VALID SALES RECEIPT, AGAINST DEFECTS IN MATERIALS AND WORKMANSHIP NOT CAUSED BY NORMAL WEAR FOR THE LIFETIME OF THE PRODUCT. FIBER OPTIC BREAKAGE OR MODIFICATION IS NEVER COVERED UNDER WARRANTY. T.R.U. INC., THE MANUFACTURER OF AXCEL SIGHTS, RESERVES THE RIGHT TO REPAIR OR REPLACE DEFECTIVE PARTS AT ITS DISCRETION. IN THE EVENT OF BREAKAGE DUE TO DEFECTIVE PARTS, THE LIABILITY OF T.R.U. INC. SHALL NEVER EXCEED THE ORIGINAL RETAIL COST OF THE PRODUCT. DEFECTS CAUSED BY NORMAL WEAR MAY BE REPAIRED FOR AN ADDITIONAL CHARGE.

FOLLOW US



TRUBALLARCHERY
AXCELSIGHTS



@TRUBALLARCHERY
@AXCELSIGHTS

AXCEL SIGHTS • 131 Crennel Dr. • PO Box 1180
Madison Heights, VA 24572 • 434-929-2800 • info@axcelsights.com

ARMORTECH-HD (AXAT-D519-BK)

5 Pins / .019 Fibers / Black



WWW.AXCELSIGHTS.COM

Patent Pending