

BASIC OLB

OptiStep®



U= 1.54
W/m²K

high insulation



easy and quick
installation



high comfort
of use



additional
accessories
available
p. 18-19

2,6
cm

WARRANTY
2
YEARS

Maximum loading	150kg
Ladder width	34cm
Tread width	7cm
Tread length	30cm
Distance between treads	25cm
Hatch thickness	2.6cm
Box height	11cm
Heat transfer coefficient*	U=1.54W/m ² K

*manufacturer's internal testing for the middle part of the hatch

Hatch

- “sandwich” type insulated hatch with a thickness of 26mm;
- finished on both sides with HDF board, white;
- equipped with a snap lock;
- opened by means of supplied control rod.

Box

- made of spruce or pine wood;
- stiffened in corners by means of a spring catch;
- equipped with clinging seal;

Ladder

- 3-section ladder;
- made of pinewood.

Treads

- treads connected to the strings by means of dovetail joints for increased connection durability;
- equipped with special anti-slipping grooves for extra security.

Available sizes

60x120, 70x120 [cm]



Energy-efficiency

2.6cm thick insulated hatch
reduces heat loss.



High aesthetics

White on the outer side, the hatch
matches perfectly with the
interior design.



Snap lock

Hatch is equipped with a snap
lock which presses the hatch
against seals.