





coflex **CTL**

COFLEX CTL expansion joints are composed of a metal structure and a flexible yet durable central infill that can be ground and polished on-site. Due to their resistance to corrosion and wear, the profiles are ideal for stone tile installations in industrial and commercial settings. The metal angle profile protects vulnerable tile edges against mechanical stress that can cause chipping and cracking; the metal flanges absorb and redistribute loads, material compression and expansion. Ideally used in retail shops, hotels, sports facilities and schools. Suggested floor bays: 172-7/32"ft² (16m²).



(CTL 150*)



COFLEX CTL-AN* Natural aluminum + Grindable Infill

Particularly suitable for car showrooms and repair shops, this profile is both resistant and modern.

Stainless steel and brass profiles are recommended for outdoors, areas subject to mechanical and chemical stress and wear.



	H = in	mm	Art.		
Material: Aluminum	5/16	8	CTL	80	AN 51/23/32
	3/8	10	CTL	100	AN 51/23/32
	1/2	12.5	CTL	125	AN 51/23/32
Finish: Natural (AN)	9/16	15	CTL	150	AN 51/23/32
	3/4	20	CTL	200	AN 51/23/32
	1	25	CTL	250	AN 51/23/32
Interni: EPDM			CTL	300	AN 51/23/32
Black (51), Cement Grey (23), Beige (32)	1-3/16	30	CTL	300	AN 51/23/32
Length: 8'10" (2.70meters)					

COFLEX CTL-ON* Brass + Grindable Infill

This profile guarantees high resistance to chemical and mechanical stress and wear. Suitable for indoor and outdoor use, in public projects and recreation facilities with classic detailing.



Material: Brass	5/16	8	CTL	80	ON 51/23/32
	3/8	10	CTL	100	ON 51/23/32
	1/2	12.5	CTL	125	ON 51/23/32
Finish: Natural (ON)	9/16	15	CTL	150	ON 51/23/32
	3/4	20	CTL	200	ON 51/23/32
	1	25	CTL	250	ON 51/23/32
Interni: EPDM			CTL	300	ON 51/23/32
Black (51), Cement Grey (23), Beige (32)	1-3/16	30	CTL	300	ON 51/23/32
Length: 8'10" (2.70meters)					

COFLEX CTL-IL* Polished Stainless Steel AISI 304 – DIN 1.4301 + Grindable Infill

This cold-rolled stainless steel profile is ideal for food processing plants, commercial kitchens, warehouses, factories and hospitals. Recommended for high traffic areas in shopping centers and restaurants. Suitable for indoor and outdoor applications with excellent resistance to corrosion.



Material: Stainless steel AISI 304	5/16	8	CTL	80	IL 51/23/32
	3/8	10	CTL	100	IL 51/23/32
	1/2	12.5	CTL	125	IL 51/23/32
Finish: Polished (IL)	9/16	15	CTL	150	IL 51/23/32
	3/4	20	CTL	200	IL 51/23/32
	1	25	CTL	250	IL 51/23/32
Interni: EPDM			CTL	300	IL 51/23/32
Black (51), Cement Grey (23), Beige (32)	1-3/16	30	CTL	300	IL 51/23/32
Length: 8'10" (2.70meters)					