

1. Product and Company Identification

Product Code: C10
Product Name: Break Away Fast Penetrating Oil
Company Name: CYCLO INDUSTRIES, INC.
902 SOUTH US HIGHWAY 1
JUPITER, FL 33477
Phone Number: (800)843-7813

Web site address: www.cyclo.com
Email address: ehs@cyclo.com

Emergency Contact: First Aid Emergency (800)752-7869
CHEMTREC (703) 527-3887 (800)424-9300

Information: First Aid Emergency (Outside U.S.) (312)906-6194

Intended Use: Penetrant

2. Hazards Identification

Flammable Aerosols, Category 1
Acute Toxicity: Inhalation, Category 4
Acute Toxicity: Oral, Category 4
Acute Toxicity: Skin, Category 4
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2



GHS Signal Word: **Danger**

GHS Hazard Phrases: H222: Extremely flammable aerosol.
H229: Pressurized container: may burst if heated.
H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.

GHS Precaution Phrases: P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P211: Do not spray on an open flame or any other ignition source.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P251: Pressurized container: Do not pierce or burn even after use.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P363: Wash contaminated clothing before reuse.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



SAFETY DATA SHEET

Break Away Fast Penetrating Oil

Revision: 08/02/2017
Supersedes Revision: 06/23/2016

P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

GHS Storage and Disposal

Phrases:

P403+235: Store in cool/well-ventilated place.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 deg C/122 F.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

Medical Conditions Generally Repeated contact with skin may irritate pre-existing skin conditions.

Aggravated By Exposure:

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-52-5	Mineral oil, petroleum distillates, hydrotreated heavy naphthenic	50.0 -70.0 %
68476-86-8	Liquified petroleum gas, sweetened	20.0 -30.0 %
108-94-1	Cyclohexanone	1.0 -5.0 %

4. First Aid Measures

Emergency and First Aid Procedures:

If swallowed, do not induce vomiting. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of skin contact, wash with soap and large amounts of water. Remove contaminated clothing. If in eyes, rinse cautiously with water for several minutes, Remove contact lenses, if present and easy to do. Continue rinsing. Call physician immediately if adverse reaction occurs.

Signs and Symptoms Of Exposure:

Eyes: Contact with eyes may cause irritation, redness and pain. Causes moderate to severe eye irritation.

Skin: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Prolonged contact with liquid may cause slight temporary irritation.

Inhalation: Prolonged inhalation may be harmful. Inhaling large quantities of mist or vapor may cause some irritation to nose, throat and lungs. Avoid breathing mists from this product. Exposure to high doses may cause central nervous system depression (anesthetic-like effects). Doses which cause anesthetic-like effects may also cause adverse effects in liver, lungs and kidneys.

Ingestion: Ingestion is not considered to be a hazard encountered in normal industrial use. This material may be harmful or fatal if swallowed. Aspiration hazard. Low order of toxicity. May cause mild nausea and abdominal discomfort.



SAFETY DATA SHEET

Break Away Fast Penetrating Oil

5. Fire Fighting Measures

Flammability Classification:	NFPA Level 3 Aerosol
Flash Pt:	-141.00 F (-96.1 C) Method Used: TAG Closed Cup
Explosive Limits:	LEL: .7 UEL: 9.5
Autoignition Pt:	No data.
Suitable Extinguishing Media:	Foam, carbon dioxide, dry chemical, alcohol-resistant foam.
Fire Fighting Instructions:	Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire. Keep containers and surroundings cool with water spray. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Flammable Properties and Hazards:	Vapors can travel to a source of ignition and flash back. Extremely flammable. Material will readily ignite at room temperatures in the presence of an ignition source. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Contents under pressure. Containers may explode if exposed to high temperatures.
Hazardous Combustion Products:	No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:	Use recommended personal protective equipment. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.
---	---

7. Handling and Storage

Precautions To Be Taken in Handling:	Keep away from heat/sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Pressurized container: Do not pierce or burn even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Keep out of the reach of children.
Precautions To Be Taken in Storing:	Store in cool/well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 deg C/122 F.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-52-5	Mineral oil, petroleum distillates, hydrotreated heavy naphthenic	No data.	No data.	No data.
68476-86-8	Liquified petroleum gas, sweetened	No data.	No data.	No data.
108-94-1	Cyclohexanone	PEL: 50 ppm	TLV: 20 ppm STEL: 50 ppm	No data.



SAFETY DATA SHEET

Break Away Fast Penetrating Oil

Respiratory Equipment (Specify Type):	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Eye Protection:	Wear safety glasses with side shields or goggles when using this product.
Protective Gloves:	Gloves resistant to petroleum distillates should be worn.
Other Protective Clothing:	Wear impervious protective clothing, including boots, gloves, protective apron or coveralls to prevent skin contact.
Engineering Controls (Ventilation etc.):	Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.
Work/Hygienic/Maintenance Practices:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin and clothing.

9. Physical and Chemical Properties

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	Light amber brown liquid with solvent odor.
pH:	No data.
Melting Point:	No data.
Boiling Point:	-94.00 C (-137.2 F)
Flash Pt:	-141.00 F (-96.1 C) Method Used: TAG Closed Cup
Evaporation Rate:	No data.
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: .7 UEL: 9.5
Vapor Pressure (vs. Air or mm Hg):	No data.
Vapor Density (vs. Air = 1):	No data.
Specific Gravity (Water = 1):	.820
Solubility in Water:	No data.
Octanol/Water Partition Coefficient:	No data.
Percent Volatile:	22.18 % by weight.
Autoignition Pt:	No data.
Decomposition Temperature:	No data.
Viscosity:	No data.



10. Stability and Reactivity

Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	Open flames and high temperatures. Contact with strong oxidizing agents. Avoid all sources of ignition, welding arcs and open flames. Keep product away from temperatures in excess of 120F (49C). Do not crush, puncture or incinerate container. Do not expose to direct sunlight or store where temperatures could exceed 120F.
Incompatibility - Materials To Avoid:	Strong oxidizing agents. Strong bases.
Hazardous Decomposition or Byproducts:	Carbon oxides; fumes.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	No data available.

11. Toxicological Information

Toxicological Information:	<p>LD50: >5000 mg/kg</p> <p>LC50: >4600 ppm</p> <p>CAS# 64742-52-5:</p> <p>Mutagenicity:, Mutation test: Mutation in microorganisms., 10.00 UL/PLAT, Bacteria - Salmonella typhimurium,.</p> <p>Results:</p> <p>Behavioral: Coma.</p> <p>Biochemical:Metabolism (intermediary): Other.</p> <p>- Cell Biology and Toxicology., Princeton Scientific Pub., Inc., 301 N. Harrison St., CN 5279, Princeton, NJ 08540, Vol/p/yr: 2,63, 1986</p> <p>Acute toxicity, LD (Lethal dose), Oral, Rat, > 5.000 GM/KG.</p> <p>Results:</p> <p>Tumorigenic: Neoplastic by RTECS criteria.</p> <p>Lungs, Thorax, or Respiration: Tumors.</p> <p>Tumorigenic:Tumors at site of application.</p> <p>- Acute Toxicity Data. Journal of the American College of Toxicology, Part B., Mary Ann Liebert, Inc., 1651 Third Ave., New York, NY 10128, Vol/p/yr: 1,133, 1990</p> <p>Acute toxicity, LD (Lethal dose), Skin, Species: Rabbit, > 5.000 GM/KG.</p> <p>Results:</p> <p>Behavioral: Coma.</p> <p>Biochemical:Metabolism (intermediary): Other.</p> <p>- Acute Toxicity Data. Journal of the American College of Toxicology, Part B., Mary Ann Liebert, Inc., 1651 Third Ave., New York, NY 10128, Vol/p/yr: 1,133, 1990</p> <p>Tumorigenic Effects:, TDLo, Skin, Mouse, 480.0 GM/KG, 80 W.</p> <p>Results:</p> <p>Tumorigenic: Neoplastic by RTECS criteria.</p> <p>Skin and Appendages: Other: Tumors.</p> <p>Tumorigenic:Tumors at site of application.</p> <p>- United States Environmental Protection Agency, Office of Pesticides and Toxic Substances., U.S. Environmental Protection Agency, Office of Pesticides and Toxic Substances, 401 M St., SW, Washington, DC 20460, Vol/p/yr: 8EHQ-0887-,</p>
-----------------------------------	--



SAFETY DATA SHEET

Break Away Fast Penetrating Oil

Revision: 08/02/2017
Supersedes Revision: 06/23/2016

Tumorigenic Effects:, TDLo, Skin, Mouse, 402.0 GM/KG, 78 W.

Results:

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria.

Skin and Appendages: Other: Tumors.

Tumorigenic:Tumors at site of application.

- British Journal of Cancer., Macmillan Press Ltd, Houndmills, Basingstoke, Hampshire RG21 2XS UK, Vol/p/yr: 48,429, 1983

Tumorigenic Effects:, TDLo, Skin, Mouse, 398.0 GM/KG, 22 W.

Results:

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria.

Skin and Appendages: Other: Tumors.

Tumorigenic:Tumors at site of application.

- British Journal of Cancer., Macmillan Press Ltd, Houndmills, Basingstoke, Hampshire RG21 2XS UK, Vol/p/yr: 48,429, 1983

Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, Severe.

Results:

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria.

Skin and Appendages: Other: Tumors.

Tumorigenic:Tumors at site of application.

- Acute Toxicity Data. Journal of the American College of Toxicology, Part B., Mary Ann Liebert, Inc., 1651 Third Ave., New York, NY 10128, Vol/p/yr: 1,133, 1990

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-52-5	Mineral oil, petroleum distillates, hydrotreated heavy naphthenic	n.a.	n.a.	n.a.	n.a.
68476-86-8	Liquified petroleum gas, sweetened	n.a.	n.a.	n.a.	n.a.
108-94-1	Cyclohexanone	n.a.	3	A3	n.a.

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method: Dispose of contents/container in accordance with local/regional/national/international regulation.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Aerosols, Ltd. Qty.
DOT Hazard Class: 2.1 FLAMMABLE GAS
UN/NA Number: UN1950

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Aerosols, Ltd. Qty.
UN Number: 1950
Hazard Class: 2.1 - FLAMMABLE GAS
IMDG EMS Page:

Packing Group:
IMDG Classification: 2.1
IMDG MFAG Number:
Marine Pollutant: No



SAFETY DATA SHEET

Break Away Fast Penetrating Oil

Revision: 08/02/2017
Supersedes Revision: 06/23/2016

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Aerosols, flammable, 2.1, Ltd. Qty.
UN Number: 1950
Hazard Class: 2.1 - FLAMMABLE GAS **IATA Classification:** 2.1

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-52-5	Mineral oil, petroleum distillates, hydrotreated heavy naphthenic	No	No	No
68476-86-8	Liquified petroleum gas, sweetened	No	No	No
108-94-1	Cyclohexanone	No	Yes 5000 LB	No

CAS # Hazardous Components (Chemical Name)**Other US EPA or State Lists**

64742-52-5	Mineral oil, petroleum distillates, hydrotreated heavy naphthenic	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
68476-86-8	Liquified petroleum gas, sweetened	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
108-94-1	Cyclohexanone	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: No; NJ EHS: No; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: No; WI Air: Yes


CAS # Hazardous Components (Chemical Name)**International Regulatory Lists**

64742-52-5	Mineral oil, petroleum distillates, hydrotreated heavy naphthenic	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
68476-86-8	Liquified petroleum gas, sweetened	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
108-94-1	Cyclohexanone	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

16. Other Information

Revision Date: 08/02/2017

Hazard Rating System:



Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting



SAFETY DATA SHEET

Break Away Fast Penetrating Oil

Revision: 08/02/2017

Supersedes Revision: 06/23/2016

from use of or reliance upon this information.