

TWISTER T4 SE

Customize Your Trim Speed

T4	Type	Feed (lbs/hr)	Feed (kg/hr)
1	Wet	Up to 23	Up to 11
2	Wet	Up to 51	Up to 23
3	Wet	Up to 81	Up to 37
4	Wet	Up to 113	Up to 51
1	Dry	Up to 7	Up to 3
2	Dry	Up to 16	Up to 7



Triple System



Tandem System



T4 SE Trimmer Features

- Lightweight
- Portable with its two-piece design
- Adjustable feet to allow incline
- 304 stainless steel tumbler
- Nitrided steel blades
- Stainless steel high air flow guard
- Scale up to 3 wet / 2 dry in a row
- Control box with digital controls
- Speed control of tumbler
- Speed control of blades
- Airflow control (Vacuum Bypass)



TWISTER T4 SE



ADDITIONAL REQUIREMENTS

Extension Cord

12 AWG (Minimum AWG Size)

7.6m / 25ft max length

T4 LEAF TRIMMER

T4 LEAF COLLECTOR

CONNECTOR (PLUG)

NEMA 5-15P



NEMA 5-15P



SPECIFICATIONS	Product Number	24-9019-00-P
	Input Voltage	115V, 60 Hz
	Current Draw	2.5A
	Blade Motor	200W
	Blade Speed	980-1875 RPM
	Tumbler Motor	6W
	Tumbler Speed	47-96 RPM
	Tumbler Diameter	5in / 10.1cm
	Tumbler Slots	40 x .25in/.6cm
	Cut Height	.040in / 1mm
	Weight	56lbs / 25.4kg
	Shipping Weight (w/ T4-LC)	120lbs / 54.4kg
	Length	25in / 63.5cm
	Width	15in / 38.1cm
Height	16.5in / 42cm	
Circuit Breaker Required	15A / 120V	
Connector (plug)	NEMA 5-15P	
Filter Bag Included	70 Micron	

ACCESSORIES & COMPONENTS	T4 Leaf Collector	23-0170-03-P
	T4 Trim Saver	23-0201-01-P
	T4 Stand (no vacuum)	23-0229-00
	T4 Stainless Steel Stand (no vacuum)	23-0030
	T4 Rail (Tandem)	24-0140-P
	T4 Rail (Triple)	24-0139-P
	Feed Conveyor (Inbound)	26-0001-02
	Quality Conveyor (Outbound)	26-0002-02
	Feed Conveyor (Extra Tall for T4 Rail)	26-0102-00

Visit twistertrimmer.com or call your Twister Rep for an extensive list of replacement parts or accessories.



TWISTER