



**NOTES:**

1. INLET: 5/16" BARB
2. OUTLETS: 5/16" BARB W/ SHUTOFF
3. GAUGES: 60# (4 EA)
4. SAFETY BLOW-OFF: 60 ± 5 PSI
5. WORKING PRESSURE: 0-50 PSI
6. POLY BONNETS WITH ADJ GOLD CAPS

MATERIAL	DRAWN	NAME	DATE
		JPK	08/02/11
FINISH	ENG APPR.		
<p><b>PROPRIETARY AND CONFIDENTIAL</b>          THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.</p>			
<p>DIMENSIONS ARE IN INCHES</p> <p>TOLERANCES:          FRACTIONAL ± 1/64          ANGULAR: MACH ± 1/2°          BEND ±          TWO PLACE DECIMAL ± 0.015          THREE PLACE DECIMAL ± 0.005</p>			



TITLE: **REG, SEC, BEER, 4P4P, 60#, 5/16B IN, 5/16B SHUTOFF, POLY, GOLD**

SIZE	DWG. NO.	REV
<b>A</b>	<b>T1694ST_SALES</b>	<b>B</b>

SCALE: 1:2      DO NOT SCALE DRAWING      SHEET 1 OF 1