

NOTES:

INLET/THRU: 5/16" BARB
OUTLETS: 5/16" BARB W/ SHUTOFF
GAUGES: 60# (3 EA)
SAFETY BLOW-OFF: 60 ± 5 PSI
WORKING PRESSURE: 0-50 PSI
POLY BONNETS WITH ADJ GOLD CAPS

MATERIAL		NAME	DATE					·
	DRAWN	JPK	08/02/11		\bigtriangledown	AP	\mathbf{K}	
FINISH	ENG APPR.				248 NORTH	WESTERN DR. SAN		
	PROPRIETARY					EC, BEER	2020	60#
DIMENSIONS ARE IN INCHES	AND CONFIDENTIAL							00#,
	THE INFORMATION CONTAINED					N/THRU, 5		
TOLERANCES:	IN THIS DRA			S	HUTO	FF, POLY	GOLD	
FRACTIONAL ± 1/64	PROPERTY OF TAPRITE-FASSCO						,	
ANGULAR: MACH ± 1/2°	MFG., INC. A	NY REPRO	DUCTION	SIZE	DWG.	NO.		REV
BEND ±	IN PART OR AS	S A WHOLI	E WITHOUT		T160	20T 2NL C		B
TWO PLACE DECIMAL ± 0.015	THE WRITTE		A	1100	33ST-2N_SALES		D	
THREE PLACE DECIMAL ± 0.005	TAPRITE-FASSCO MFG., INC. IS PROHIBITED.			SCAL	E: 1:2	DO NOT SCALE DRAWING	SHEE	T 1 OF 1