

NOTES:

1. INLET/THRU: 5/16" BARB

2. OUTLETS: 5/16" BARB W/ SHUT-OFFS

3. GAUGES: 60#

4. SAFETY BLOW-OFF: 60 ± 5 PSI. 5. WORKING PRESSURE: 0-50 PSI 6. BONNETS: POLY, GOLD

MATERIAL		NAME	DATE						_
	DRAWN	DWH	08/19/09	•		AF	7	TT	
FINISH	ENG APPR.			32	48 NORTH	WESTERN DR.			
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO			TITLE: REG SEC BEER, 5P5P,60#, 5/16B IN/THRU, 5/16B SHUTOFF, POLY GOLD					
ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015	MFG., INC. A IN PART OR AS THE WRITTE	NY REPRO S A WHOLE EN PERMIS	DUCTION WITHOUT SION OF	SIZE A	DWG. T169	NO. 5ST-2N	_SAL	ES	REV -
THREE PLACE DECIMAL ± 0.005	TAPRITE-FA	ASSCO MF	G., INC.	CCAI	T. 1.1	DO NOT SC	ALE	CHEE	T 4 OF 4

IS PROHIBITED.

DO NOT SCALE DRAWING

SHEET 1 OF 1

SCALE: 1:1