


NOTES:

1. INLTET: 1/4" SAE FLARE
2. OUTLET: 1/4" SAE FLARE WITH BALL CHECK
3. GAUGES: 160 PSI
4. SAFETY BLOWOFF: 130 ± 4 PSI
5. WORKING PRESSURE: 0-120 PSI
6. BONNET: POLY WITH GOLD ADJ CAP

MATERIAL	NAME	DATE	 3248 NORTHWESTERN DR. SAN ANTONIO, TX 78238
	DRAWN	JPK	
FINISH	ENG APPR.		TITLE: REG SEC SODA, 160# 1/4F IN/THRU W/CAP, 1/4F-CV, POLY GOLD
	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		SIZE DWG. NO. REV A T5261SN-160_SALES B
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005			SCALE: 1:2 DO NOT SCALE DRAWING SHEET 1 OF 1