


**NOTES:**

1. INLET: TANK FITTING
2. OUTLET: 1/4" BARB WITH BALL CHECK AND SHUTOFF
3. GAUGE: 160# REG. GAUGE  
2000# TANK GAUGE (NON UL)
4. SAFETY BLOW-OFF:  $130 \pm 4$  PSI
5. WORKING PRESSURE 0-120 PSI
6. POLY BONNET, BLACK

MATERIAL	NAME	DATE	 3248 NORTHWESTERN DR. SAN ANTONIO, TX 78238 <b>TITLE: REG. PRI SODA, 160#,          TNK FTG, 1/4B -CV SHTFF,          2000#, POLY, BLACK</b>
	DRAWN	JRS	
FINISH	ENG APPR.		SIZE DWG. NO. REV <b>A</b> T5741PMHPBK-01_SALES <b>A</b>
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/64$ ANGULAR: MACH $\pm 1/2^\circ$ BEND $\pm$ TWO PLACE DECIMAL $\pm 0.015$ THREE PLACE DECIMAL $\pm 0.005$		<b>PROPRIETARY AND CONFIDENTIAL</b> THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.	
SCALE: 1:2		DO NOT SCALE DRAWING	<b>SHEET 1 OF 1</b>