



NOTES:

1. INLET: 1/4" FLARE
2. OUTLETS: 1/4" FLARE WITH CHECK (2 EA)
3. GAUGES: 160#, 100#, 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI.
5. WORKING PRESSURE: 0-120 PSI
6. BONNETS: POLY, BLACK
7. S/S REG. BRACKET (2)
8. 6' HIGH PRESSURE HOSE

MATERIAL	NAME	DATE
	DRAWN	JRS 11/12/10
FINISH	ENG APPR.	
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2" BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE:
**REG, PRI, SODA, WM, 2P2P,
 160#/100#, 1/4F IN/OUT, 2000#,
 POLY, RED/GOLD, 6' HOSE**

SIZE	DWG. NO.	REV
A	T8871-6_SALES	A