

Adhesives & Fastening Products

355 Hollow Hill Drive Wauconda, IL 60084 Ph: 847.487.4583 Fax: 847.487.0174 E-mail: sales@surebonder.com Website: surebonder.com

Specification Sheet #708

Type: Hot Melt Glue - Ethylene Vinyl Acetate

Solids: 100%

Viscosity: @ 250°F 37,600 cps

@ 325°F
 @ 350°F
 @ 375°F
 5,600 cps

Softening Point: 185/F
Color: TAN
Odor: Slight
Shelf Life: Indefinite
Flash Point: Above 450/F

FDA Status: Compositional compliance with FDA Regulation

#21CFR175.105 for food packaging.

Suggested Uses: Excellent carpet backing adhesive. Resists

cracking at low temperatures and rigid to prevent

"smiling". Excellent for corrugated.

Storage: Common Storage

Application Temperature: 250/F to 380/F

Precautions: Do Not Mix with other adhesives

Severe burns will result if contact is made in molten

state.

Material safety data sheets providing safety

precautions that should be observed in handling

and storing.

The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. FPC warrants that the product conforms with FPC written specifications, and is free from defects. FPC disclaims all other warranties, expressed or implied, including the warranties of merchantability and fitness for a particular purpose. The buyer's sold remedy for non compliance with this warranty shall be for the replacement of the product or refund of the buyer's purchase price.