

**Specification Sheet
B-10530**

Type:	Hot Melt Adhesive		
Solids: Viscosity ¹ :	100%		
	@ 300° (F) (cps)	2,235	
	@ 325° (F) (cps)	1,330	
	@ 375° (F) (cps)	850	
Softening Point ² :	172° (F)		
Color:	Colorless		
Shelf Life:	730 days in a clean dry place, in its original package at an average temperature of 25°C or below		
Flash Point:	Above 399° (F)		

Storage: Common Storage. Storage temperature should not exceed 40°C.

Application Temperature: 300°F - 350°F

Suggested Uses: Is a high tack, peelable, resealable, pouch seal pressure sensitive hot melt adhesive that is food grade safe. Can be used for many packaging applications.

Precautions: Do Not Mix with other adhesives
Severe burns will result if contact is made in molten state.
Material safety data sheets provide safety precautions that should be observed in handling and storing.

The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. FPC warrants that the product conforms with FPC written specifications, and is free from defects. FPC disclaims all other warranties, expressed or implied, including the warranties of merchantability and fitness for a particular purpose. The buyer's sole remedy for non compliance with this warranty shall be for the replacement of the product or refund of the buyer's purchase price.

¹ Brookfield Viscosity – ASTM D3236 using spindle SC4-27

² Softening Point (Ring and Ball Herzog - ASTM E28)