










POP-UP POWERING

Outlet Type	Docking Drawer Pop-Up Powering™ 	Docking Drawer Pop-Up Powering™ 	Docking Drawer Pop-Up Powering™ 	Docking Drawer Pop-Up Powering™ 
Outlet Name	Pop-Up Powering (15amps)	Pop-Up Powering (20amps, GFCI)	Pop-Up Powering (20amps, GFCI, USB-A)	Pop-Up Powering (20amps, GFCI, USB-A, QI)
Part Number	0290-70002	0290-80000	0290-80001	0290-80002
Finish Choices	White, Black and Stainless Steel			

CABINET SPECIFICATIONS

Cut-Out Diameter				
Bezel Diameter	4.875"			
Height Above Countertop	6.5"	5.625"	7.5"	
Depth Under 1.25" Counter	9.25"	9"	10.5"	
Counter Thickness Limits	0.375" - 2.1875"			
Flange Width Under Counter	4.9375"			

RECEPTACLE SPECIFICATIONS

				
Tamper Resistant Plugs	Yes			
120V AC Outlets	2			
USB Ports	2 USB-A	0	2 USB-A	
Max Current (USB)	3.6 amps @ 120 VAC	NA	2.1 amps (Shared)	
GFCI	0	Yes		
Max Current	15 amps	20 amps		

ASSEMBLY SPECIFICATIONS

Wireless Qi Charging Top	Yes	No	Yes
ETL Listed	Yes		
CSA Listed	Yes		
Water Protection Closed	IP54 Spill Proof rated		
Water Protection Open	1/2 gallon spill rated outlet		
Interlocking Safety Feature	No		
Electrical Connection	9' cord with 3 prong plug		
Warranty	1 year		