



EXTRALINK 12 POE INJECTOR GIGABIT



DESCRIPTION

The 12 gigabit port PoE panel is using 10/100/1000M Ethernet, Each socket provides protection against short overflow (current protection 650mA±15%). The configuration size of panel is: 1U (height), 19" (width) and 52mm (thickness).

FEATURES

- 10/100/1000M Ethernet ports
- Flexible power (DC 18V TO 57V)
- Each Port Current Protection (650mA)
- For 19" Rack Mount (1U)
- 4 LED status indicators
- Ideal for IP cameras,VOIP phone,WiFi Access Point

SPECIFICATIONS

Color	Black
Input	100-240V AC 50/60Hz
Output	18 TO 57 V 120W
Data	1/2&3/6&4/5&7/8
Power	3/6+ & 1/2-, 4/5+ & 7/8-
Weight	1.2kg
Dimensions	482.6mm x 44.3mm x 52mm
Case of material	Metal work material
Ethernet Cable	TIA/EIA 568 Cat. 5
Data rate	10/100/1000Mbps
Connector	RJ-45
Operating Temperature	0°C ~ 40°C
Storage Temperature	-40°C~+70°C
Operating Humidity	10%~80% RH
Storage Humidity	5%~90%RH
Certification	CE