



Proudly brought to you by
The Painted Brush & Co
www.thepaintedbrush.com.au

AUTENTICO® Crackle Glaze

Product Description:

Autentico® Crackle Glaze is an exciting decorative medium which can age and distress your furniture with one even coat.

Autentico® Crackle glaze is a one-step product to create a crackled effect between layers of Autentico® Vintage Furniture paint for the ultimate shabby chic effect. Ideal for smaller items to produce a consistent 'chippy' look.

Location:

Interior.

Suggested Applications:

Can be applied to furniture, skirting, architrave, pottery, picture frames and more.

Preparation:

Autentico® Crackle Glaze should be applied only when the painted substrate is fully dry, clean and stable.

Application:

Firstly we recommend always try the technique on a test piece before starting the project. Walls and vertical surfaces need a lot of practice. Choose a colour from the Autentico® Vintage Furniture Paint colour palette for the base coat – (the colour of the cracks) the other for the topcoat. Apply the base coat of Autentico Vintage and allow to dry.

Apply the crackle glaze evenly either in a constant zig zag nature or a traditional long even brush strokes. The coat must be smooth and even, if not, remove the glaze with a damp cloth, and reapply working it into the surface before applying of to a smooth even coat. Allow to dry.

Apply the topcoat of Autentico Vintage Furniture Paint, load your brush with generous amount of paint and apply in one direction only, if paint beginnings to pull, reload brush and reapply but always in the same direction. The thickness of the topcoat determines the size of the cracks – the thicker the coat the wider the cracks. Cracking occurs immediately as the paint dries, revealing the base colour through the cracks. Leave to dry for 24 hours and protect with Autentico Soft Wax or Autentico Matt Varnish for extra protection is required.

Drying time:

15mins to 1 hr - depending on temperature

Coverage:

Approx. 2m² per 250ml tin dependent on surface porosity.

Packaging:

Autentico® Crackle Glaze is available in 250ml.

Limitations:

All Autentico products should not be applied in high humidity, below 10°C or above 30°C.

Storage:

Keep in a cool dry place. Away from risk of frost.

Cleaning and Disposal:

Clean tools equipment with warm soapy water, rinse well with clean water, and allow to dry naturally. Do not empty containers into drains or watercourses.

Environmental Information:

Water based, Non-hazardous and low odour.

Autentico® Paint uses only the finest quality, low odour and minimal environmental impact raw materials. Our manufacturing processes are zero waste and all paint formulations are designed for maximum performance with minimum impact on user health.

This product is formulated by Polyvine®. All technical product information and data sheets can also be found on their website: www.polyvine.com

Health and Safety:

Keep out of reach of children. Contact with eyes-wash immediately with warm water consistently with eye lids open for at least 10 minutes.

Manufacturers Details:

Unit 4, The Glenmore Centre
Moat Way
Ashford
Kent
TN24 0TL

01233878303

www.autentico-paint.com
enquiries@autentico-paint.com