



Copyright MAXAM

## TECHNICAL DATA SHEET

### MAXAM 175 Emergency Glazing Repair film

#### **Manufacturer:**

MAXAM, 14 Cultins Road, Edinburgh EH11 4DZ

#### **Product Certification:**

BS EN 12600 1B1 Impact resistance

RSSB1024 Approved BR Cat ref 59/165062

#### **Main Usage:**

Applying to broken and unsafe glass windows in:

- Housing
- Public buildings
- Trains
- Commercial buildings

#### **Technical Data:**

Type of film: Semi rigid CPET Polyester 175u

Colour: Clear transparent

Type of adhesive: Solvent based

Coating weight: 45gsm

Lining: Silicone coated paper

Overall thickness: Min 215u

#### **Product performance:**

DYNAMIC SHEAR - MINIMUM 160 N/25mm<sup>2</sup>

PEEL ADHESION – MINIMUM 18 N/25mm

#### **Product size:**

Various width X various lengths

**Storage:**

Normal room conditions -20°C to +40°C

**Application:**

- Surface can be dry or slightly damp
- Cut to size
- Peel backing off along top edge and apply to window
- Pull remaining paper off whilst smoothing over broken glass with soft cloth
- If possible apply to both sides of the glass for extra safety
- For larger areas overlap by 10cm

**Note:****Copyright MAXAM:**

MAXAM treats its intellectual property very seriously and does not hesitate to take legal action where its rights and intellectual properties are compromised. The specifications, performance figures and certification listed in this document are all property of MAXAM and copyright MAXAM.

Please address any further questions or queries to:

T: 0131 4424343

E: [info@maxam.co.uk](mailto:info@maxam.co.uk)

MAXAM 14 Cultins Road, Edinburgh EH11 4DZ