

Recommended Tire Size																							
Tire size	23mm	25mm	28mm	30mm	32mm	35mm	37mm [1.5"]	40mm [1.6"]	42mm [1.7"]	44mm [1.7"]	47mm [1.9"]	50mm [2.0"]	52mm [2.0"]	54mm [2.1"]	55mm [2.2"]	57mm [2.2"]	58mm [2.3"]	60mm [2.4"]	62mm [2.4"]	64mm [2.5"]	67mm [2.6"]	70mm [2.8"]	76mm [3.0"]
Max. Tire Pressure [psi]	110		100	80		70		50			40			35			30			25			
Inside rim width, mm (ETRTO Rim Size)	<div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 70%;"> <p>ROAD, 19C/20C: Veil, Radiant, Solstice, Leviathan (TC)</p> <p>TANDEM/LOADED TOURING, 19C/20C : Leviathan (TC)</p> <p>TANDEM/ LOADED TOURING, 22C/25C: Wanderlust, Outback (TC)</p> <p>ALL-ROAD, 23C: Wanderlust Carbon* (TC) GRAVEL</p> <p>ALL-ROAD, 25C: Luna, Luna Carbon (TC) GRAVEL</p> <p>GRAVEL, 22C: Wanderlust (TC) XC MTN</p> <p>GRAVEL, 25C: Outback (TC) XC MTN</p> <p>GRAVEL, 25C: Outback Carbon 29" ONLY (TSS) XC MTN</p> <p>GRAVEL, 28C: Outback Carbon 27.5" ONLY (TSS) XC MTN</p> <p>ALL MTN, 30/32C: Serpentine, Backbone (TC & TSS)</p> </div> <div style="width: 25%; border: 1px solid black; padding: 5px;"> <p>KEY</p> <ul style="list-style-type: none"> ROAD TANDEM/LOADED TOURING ALL-ROAD GRAVEL XC MTN ALL MTN </div> </div>																						
	<p>Maximum pressure: If there is a difference between our maximum recommended pressure and the tire manufacturer's recommended maximum pressure, use the lower of the two.</p> <p>TSS (hookless) models allow a max of 50 psi when using smaller tires than recommended.</p> <p>Maximum pressures are for single bikes unless otherwise noted TC: Tubeless Clincher, TSS: Tubeless Straight sidewall (AKA Hookless)</p> <p>*Rims with Wanderlust Carbon name built before 2022 do not allow tires smaller than 32mm because they are designed to ETRTO 2020 specification (SN A0027700 and below)</p>																						