


TECHNICAL REQUIREMENTS:	
CATILEVER STRENGTH	1000# [4.55KN]
TENSILE STRENGTH	2000# [9.1KN]
TORSION STRENGTH	2500# [0.29 KN.M]
COMPRESSION STRENGTH	20000# [89KN]
NEMA VOLTAGE RATING	4.8KV
60HERTZ WITHSTAND-DRY	19KV
60 HERTZ WITHSTAND-DEW	15KV
IMPULSE WITHSTAND	60KV
APPLICABLE STANDARD	ANSI C29.10-1989

REV. #:	REVISED BY:	DESCRIPTION:		
		<b>INDOOR BUS SUPPORT</b>		
MATERIAL	SIZE	PART NO.	REV	
CYCLOALIPHATIC EPOXY	<b>A</b>	<b>A20-1-OC</b>		
FINISH	SCALE: NTS	WEIGHT:	SHEET 1 OF 1	
DO NOT SCALE DRAWING				



**Meister International, LLC**  
Serving the needs of the Global Electric Power Industry  
513-923-2712  
www.meisterintl.com 1308 US ROUTE 50, SUITE 200, MILFORD, OH 45150

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MEISTER INTL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MEISTER INTL. IS PROHIBITED.