

ML-WM-2284/2285/2286

LED SURFACE MOUNT LIGHT

DESCRIPTION

This trapezoid full cut-off wall pack is elegant as it is functional. With high performance LEDs and long lasting driver, this fixture provides effective lighting all around. It can be used around factories, restaurants, shopping centers, etc.



Specification Features



Construction

► Industrial grade die-cast aluminum alloy body is tough on the elements and allow the luminaire to withstand the harshest of conditions.

Optical System

► Next generation LEDs combined with the best-in-class UV stablized commercial grade polycarbonate lens provide the most efficient lighting system. Optical system is engineered to provide professional grade light distribution and uniformity.

Electrical

► Long lasting LED coupled with UL Listed Drivers provide an electrical system that will stand the test of time. Universal voltage allow the luminaire to be used in multi-faceted environments.

Finish

► Luminaire is electrostatically coated with UV stabilized powder coat providing years of worry-free service.

Certification

► cUL and UL Listed. Listed for Wet Locations. DLC Premium certified.

Ordering information

Model No.	System Watts	Input Voltage	CRI	Color Temp	Finish	Reflector	Option
ML-WM-2284	30W	120-277 VAC	70+	3000 K	Bronze	Forward Throw	No Sensor
	50W			4000 K			Photocell
72W	5000 K			Occupancy Sensor			
ML-WM-2285	30W	120-277 VAC	70+	3000 K	Bronze	Wide Throw	Emergency Driver
	50W						10KV Surge
72W							
ML-WM-2286	40W						

* DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.

Product Description



Included Quick Mount plate for easy and contractor friendly installation.




Low glare lens providing visual comfort.






Smart controller for a range of wattages to choose from (70W series only)




Product Dimensions





ML-WM-2284



ML-WM-2285



ML-WM-2286



Available Options



ML-WM-2284



ML-WM-2285



ML-WM-2286






Forward Throw (FT)



Wide Throw (WT)



Up & Down (U&D)



Performance Data

* Lumen and Efficacy shows the highest wattage at 5000K

Model NO.	System Watts	Lumens	Efficacy
ML-WM-2284	30W	3811 lm**	131 lm/W**
	50W	6410 lm**	125 lm/W**
	15/30/50/72W	8407 lm**	117 lm/W**
ML-WM-2285	30W	3811 lm**	131 lm/W**
	50W	6410 lm**	125 lm/W**
	15/30/50/72W	8621 lm**	120 lm/W**
ML-WM-2286	40W	6056 lm**	151 lm/W**

* DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.