



## FUEL & LUBRICANT DELIVERY & SUCTION HOSE

### FEATURES:

- Alfagomma T-605 AA.
- 10 Bar (150psi rated).
- Supplied 1/2" through to 2".
- Tube: black conductive NBR.
- Reinforcement: high tensile textile cords with embedded steel helix wire.
- Temperature: -30°C +80°C (-22°F +176°F).
- Cover: black CR - abrasion, ozone and hydrocarbon resistant.
- Specially designed for tank truck and general industrial applications.
- Safety factor: ≤127mm 3:1 133-254mm 2.5:1 305mm 1.5:1.

### RANGE OPTIONS:

Code	Description/Size	Inlet	Outlet	Connection
HOSE-12.7ID-10ML-CATA	13mm ID Hose x 10m Long	BSP	BSP	Male each end
HOSE-19ID-4ML-CATA	19mm ID Hose x 4m Long	BSP	BSP	Male each end
HOSE-FO8945000-CATA	Farm 19mm ID Hose x 6m Long	BSP	BSP	Male each end
HOSE-19ID-6ML-CATA	19mm ID Hose x 6m Long	BSP	BSP	Male each end
HOSE-19ID-10ML-CATA	19mm ID Hose x 10m Long	BSP	BSP	Male each end
HOSE-25ID-4ML-CATA	25mm ID Hose x 4m Long	BSP	BSP	Male each end
HOSE-FO8858000-CATA	Farm 25mm ID Hose x 6m Long	BSP	BSP	Male each end
HOSE-25ID-6ML-CATA	25mm ID Hose x 6m Long	BSP	BSP	Male each end
HOSE-25ID-10ML-CATA	25mm ID Hose x 10m Long	BSP	BSP	Male each end
HOSE-32ID-10ML-BSP-CATA	32mm ID Hose x 10m Long	BSP	BSP	Male each end
HOSE-38ID-10ML-BSPNPT-CATA	38mm ID Hose x 10m Long	BSP	NPT	Male each end
HOSE-50.8ID-10ML-BSP-CATA	50.8mm ID Hose x 10m Long	BSP	BSP	Male each end
HOSE-50.8ID-10ML-BSPNPT-CATA	50.8mm ID Hose x 10m Long	BSP	NPT	Male each end