



## SWIVEL BREAKAWAY COMBO 66SB DUAL PLANE RANGE

Item code: 66SB-7575 + 66SB-1010

The OPW 66SB Swivel Breakaway is intended for easy installation at the nozzle inlet. The compact, lightweight design incorporates a 360° swivel rotation at both the male end and middle joint, with a simple and easily reconnectable breakaway on the opposite end.

Available in 1" (25mm) and 3/4" (19mm) suitable for up to 10% Ethanol.

### FEATURES:

- UL and ULC listed for use in gasoline, diesel, and up to 10% ethanol blends.
- Pull force - the 66SB will break away with a pull force of no more than 350 lbs.
- Easily reconnected at waist height - after relieving line pressure, simply push coupling halves together until latched. Reconnection force is approximately 15 lbs.
- Protected coupling and poppet - the breakaway's poppet and sealing surface are protected from impact during separation by a plastic sleeve.
- Reduces connections - the single-unit design replaces the standard swivel, breakaway and whip hose, eliminating possible leak points.
- Double O-Ring seal - both swivel joints are protected by a double O-Ring design.
- Design Working Pressure - 50 PSI (3.45 bar) maximum pressure.

### Materials:

- Body: Aluminum
- Sleeve: Nylon, HDPE
- Seals: Viton®
- Spring: Stainless Steel
- Poppet: Aluminum

### PRODUCT RANGE:

Code	Description
66SB-7575	3/4" (19mm)
66SB-1010	1" (25mm)