



## UNFILTERED VENTS

All Banlaw filtered and unfiltered tank vents include a float valve shutoff for automatic refuelling shut-off systems.

They are designed to allow air to be released from the fuel tank rapidly during highspeed refuelling processes, whilst avoiding premature nozzle shut-off, along with fuel spills and sprays.

Banlaw vents are available in unfiltered, filtered, and ultra-fine filtered variants.

Part Number	Product Description	Tech Specs	Shipping Specs	Compatible Products
AUS25A	Standard Vent Unfiltered 2" NPTM, 16psi	2" NPTM 16PSI	34 x 11 x 8cm   1.1kg	2" NPT Half Coupling AUS25AA-1
AUS25A-A	Standard Vent Unfiltered 2" NPTM, 16psi, w/ Coupling			
AUS25A-A-L	Light Vent Unfiltered 2" NPTM, 7psi, w/ Coupling	2" NPTM, 7PSI		
AUS25A-C	Standard Vent Unfiltered 2" NPTM, 16psi, w/ Hose Barb DN20	2" NPTM, 16PSI		
AUS25A-C-L	Light Vent Unfiltered 2" NPTM, 7psi, w/ Hose Barb DN20	2" NPTM, 7PSI		
AUS25A-CN	Standard Vent Unfiltered 2" NPTM, 16psi, w/ NPTM Nipple DN20	2" NPTM, 16PSI		
AUS25A-L	Light Vent Unfiltered 2" NPTM, 7psi	2" NPTM, 7PSI	1.03kg	
AUS25B	Standard Vent Unfiltered Caterpillar Flange, 16psi	2" NPTM 16PSI		
AUS25B-C	Standard Vent Unfiltered Caterpillar Flange, 16psi, w/ Hose Barb DN20			
AUS25B-C-L	Light Vent Unfiltered Caterpillar Flange, 7psi, w/ Hose Barb DN20	2" NPTM, 7PSI		
AUS25B-L	Light Vent Unfiltered Caterpillar Flange, 7psi			
AUS25C	Standard Vent Unfiltered 2" NPTM, 16psi, Extended	2" NPTM, 16PSI	44 x 11 x 8cm 1.19kg	
AUS25C-A	Standard Vent Unfiltered 2" NPTM, 16psi, Extended w/ Coupling			
AUS25C-A-L	Light Vent Unfiltered 2" NPTM, 7psi, Extended w/ Coupling	2" NPTM, 7PSI		
AUS25C-C	Standard Vent Unfiltered 2" NPTM, 16psi, Extended, w/ Hose Barb DN20	2" NPTM, 16PSI		
AUS25C-CN	Standard Vent Unfiltered 2" NPTM, 16psi, Extended w/ NPTM Nipple DN20			
AUS25C-L	Light Vent Unfiltered 2" NPTM, 7psi, Extended	2" NPTM, 7PSI	1.21kg	
AUS25D	Standard Vent Unfiltered Caterpillar Flange, 16psi, Extended	FLANGE, 16PSI		
AUS25D-C	Standard Vent Unfiltered Caterpillar Flange, 16psi, Extended w/ Hose Barb DN20			
AUS25R	Light Vent Unfiltered 2" NPTM, Rail 7psi	2" NPTM, 7PSI	28 x 11 x 8cm   0.88kg	
AUS25R-B	Light Vent Unfiltered 2" NPTM, Rail 7psi, Extended			

# PETRO Contact Information

## AFRICA

### South Africa

Factory 14 Bentonite Street  
Alrode, Alberton, Johannesburg  
South Africa  
P: +27 (0)11 864 7758  
F: +27 (0) 11 864 1649  
E: sales@petroindustrial.co.za

## UAE

### Dubai

Office LB17330, Lobby Building 17  
Jebel Ali Free Zone  
PO Box 18602  
Dubai, United Arab Emirates  
P: +971 488 76688  
F: +971 488 76932  
E: salesuae@petroind.com

## AUSTRALIA

### Eastern Australia

Factory 2, 106 Potassium Street  
PO Box 407  
Narangba QLD 4504  
P: 07 3204 9558  
F: 07 3293 4852  
E: sales@petroindustrial.com.au

### Western Australia

173 Mulgul Road, Malaga WA 6090 AU  
P: +61 (8) 6305 0855  
E: saleswa@petroperth.com.au

# PETRO INDUSTRIAL



[petroind.com](http://petroind.com)