

# PETRO INDUSTRIAL



petroind.com



## FILTRATION KIT

Item code: SP-P506073-CATB

This kit uses two high performance filters, in series, to clean your diesel. The first filter removes particulate contamination from diesel. Rated at  $<4\mu\text{m}@2000$  (99.95% single pass), it is designed to target a cleanliness of ISO 14/13/11 in a single pass. The second filter uses a super absorbent polymer (SAP) that will not allow free water to pass.

This combination of filters will ensure that your diesel is both clean and dry, for maximum performance. For complete protection, Donaldson recommends installing a T.R.A.P breather to keep air-borne contamination and moisture from entering your tank.

### KIT CONTENTS:



2 x 1 1/4" NPT Single Heads.  
Code: P570330



1 x 1 1/4" NPT Threaded adaptor  
(41mm L). Code: P573642



1 x  $<4$  Micron @ Beta 2000 Filter  
Element. Code: DBB8666



1 x SAP Water absorbing Filter.  
Code: DBB0248



2 x 1/8" NPT - 0 to 60 psi  
Pressure Gauges.  
Code: P573681



2 x Gauge Adaptors. Inlet: 6/16" - 18  
UNF" Male, Outlet: 1/8" NPT Female  
(43mm L). Code: P73682

### SPECIFICATIONS:

- Flow Rate: to 189Lpm.
- Max, Working Pressure: 350psi.
- Connections: 1.25" NPT.

### APPLICATION:

- Service Vehicles.
- Fixed and/or Mobile Bulk Tanks.
- Industrial, Agriculture, Mining, Transport.