

PETRO INDUSTRIAL



petroind.com



OFF-LINE FILTRATION

Donaldson provides off-line filtration and fluid transfer capabilities in convenient portable packages. Use them in your workshop, with in-plant machinery, or mobile equipment to achieve and maintain the ISO cleanliness standard of your fluids.



Bu.F.S.S. Bulk Fuel Service System



Bu.F.S.S. 12V Bulk Fuel Service System



B.O.S.S. Bulk Oil Service System



B.O.S.S. Lite Bulk Oil Service System

Part Number	P506057	X011408	P506037	P506081
Replacement Filter Elements	DBB8666 Fuel Filter & DBB0248 Water Absorbing Filter		DBB8664 Oil Filter	P565183 Bulk hP Filter
Optional Filter Elements	DBB8777 Fuel Filter DBB7733 Compact Fuel Filter DBB5333 Compact Fuel Filter		DBB8665 Oil Filter & DBB0248 Water Absorbing Filter	P565184 Bulk hP Filter P565185 Bulk hP Filter
Target ISO Cleanliness	14/13/11 or better		18/16/13 or better	
Fluid Compatibility	All diesel fuels		Hydraulic, gear, transmission and engine oils	
Micron Rating & Efficiency	<4 micron @ Beta 2000		25 micron @ Beta 2000	14 micron @ Beta 2000
Water Absorbing Filter	Stops all free and emulsified water (optional for P506037)			n/a
Power Consumption	240 Volt 50 Hz with 2m cable	12V 35 Amp max	240 Volt 50 Hz with 2m cable	240 Volt 50 Hz with 2m cable
Max. Flow Range	63 lpm @ 2800 RPM	57 lpm @ 2900 RPM	40 lpm @ 1450 RPM	6 lpm @ 1450 RPM
Pump	Vane pump	Vane pump	Gear pump	Gear pump
Dimensions	H=1300mm W= 550mm D= 700mm	H= 576mm W= 521mm D= 186mm	H= 1300mm W= 550mm D= 700mm	H = 430mm W = 435mm D = 155mm
Weight	65 Kgs	34 Kgs	65 Kgs	14 Kgs