



900 Series

4 DIGIT (WHEEL) MECHANICAL METER RANGE

Item code: FILLRITE-METER4

Fill-Rite's line of 4 wheel mechanical flow meters are designed to meet the stringent demands of customers who need to monitor fuel usage accurately and dependability.

Rugged construction, easy to read numbers, and the flexibility of horizontal or vertical positioning are just three features of these superior meters. Plus, all can be field calibrated for the utmost accuracy, regardless of fluid.

FEATURES:

- For transfer pumps with a flow rate of 23 -151 lpm.
- UL/cUL listed.
- Rated for Gasoline, Diesel, Kerosene, mineral spirits, Stoddard solvents and heptane.
- Flow ports can be positioned vertically or horizontally.
- Handles fluid of any viscosity.
- 4 wheel mechanical meter.
- Large easy to read display.
- Provide precision and durability in a cost-effective design.

RANGE OPTIONS:

Code	Inlet/Outlet	Flow Rate	psi	Accuracy	Thread	Nickel Plated	Pump Fittings	UL/cUL CE Listed
901	25mm (1") FF	6-40gpm	50	+/- 2%	NPT	-	-	✓
9011.5	40mm (1.5") FF	6-40gpm	50	+/- 2%	NPT	-	-	✓
901L	25mm (1") FF	23-151lpm	50	+/- 2%	NPT	-	-	✓
901L1.5	40mm (1.5") FF	23-151lpm	50	+/- 2%	NPT	-	-	✓
901LMK300	40mm (1.5") FF	23-151lpm	50	+/- 2%	NPT	-	✓	✓
901LN1.5	40mm (1.5") FF	23-151lpm	50	+/- 2%	NPT	✓	-	✓
901MK300	25mm (1") FF	6-40gpm	50	+/- 2%	NPT	-	✓	✓
901MK4200	25mm (1") FF	6-40gpm	50	+/- 2%	NPT	-	✓	✓
901N1	25mm (1") FF	6-40gpm	50	+/- 2%	NPT	✓	-	✓