

# PETRO INDUSTRIAL



petroind.com



## 1:1 FAST-BALL PUMP RANGE

Item code: GRACO-FASTBALL-1:1

Typical Fluids Handled are Petroleum- and synthetic-based oils. Typical applications are continuous duty, maintenance facility dispensing motor oil, gear oil, automatic transmission fluid, hydraulic fluid.

### FEATURES:

- In-line design with fewer parts for less pump wear.
- Differential air motor ensures smooth pumping.
- Double-acting pump provides reliable fluid flow.

### SPECIFICATIONS & PERFORMANCE:

- Cycles per Gallon: 10 (45.5 liters)
- Fluid Flow gal/min @ 80 cpm: 5 (19 liters)
- Maximum Fluid Pressure: 180 psi (12.5 bar)
- Air Motor Effective Diameter: 1.4 in (35.6 mm)
- Air Operating Range: 40-180 psi (2.7-12.5 bar)
- Approx. Air Use and Flow @ 100 psi and 80 cpm: 5 scfm
- Wetted Materials: CS, Polyurethane
- Air Inlet Port Size: 1/4 in npt(f)
- Fluid Inlet Port Size: 1-1/2 in npt(f)
- Fluid Outlet Port Size: 3/4 in npt(f)
- Line Length: Up to 100 ft (30.5 m)
- Dispense Points: 1 (not recommended with hose reel)
- Annual Usage: Up to 5,000 gal (19,000 l)

### PRODUCT RANGE:

Code	Description
222051	Universal
222103	Bung Mounted
222104	1000L IBC Bung mounted
222602	Non Metered Dispensing Kit
239702	Metered Dispensing Kit