



15:1 FIRE BALL 300 UNDERCOATING/ RUST-PROOFING PACKAGES

Item code: GRACO-300-15:1-UNDERCOAT

Typical fluids handled are undercoating and rust-proofing.

FEATURES:

- Available in carbon steel for petroleum-based or SST for water-based materials.
- Durable air motor provides trouble-free operation.

TYPICAL APPLICATIONS:

- Undercoating, rust-proofing and sound-deadening materials.
- Automotive and heavy-duty vehicle dealerships.
- Fast lube centers and service shops.
- Fleet service facilities.

SPECIFICATIONS:

Maximum Fluid Pressure:	2700 psi (186 bar)
Effective Air Motor Diameter:	3 in (76.2 mm)
Operating Range:	40-180 psi (2.8-12.5 bar)
Continuous-Duty Flow Rate:	0.7 gpm (2.7 lpm)
Approx. Air Consumption @ 100 psi (7 bar):	17 cfm
Air Inlet:	3/8 npt(f)
Material Outlet:	1/4 npt(f)
Material Inlet for Non-SST Pump:	1 npt (straight inlet)
Material Inlet for 224825 (SST Pump):	1 npt (barbed inlet)
Wetted Parts for Non-SST Pump:	CS, Aluminum, PTFE, Rubber
Wetted Parts for SST pump:	SST, Aluminum, Leather, PTFE, Rubber
Instruction Manual for non-SST Pump:	306531
Instruction Manual for SST Pump:	308069

PETRO INDUSTRIAL



petroind.com



ORDERING INFORMATION:

	Undercoating			Spray Masking
	Portable	Portable Dolly-Mounted	Stationary	Bung-Mounted Stationary
Style	Portable	Portable Dolly-Mounted	Stationary	Bung-Mounted Stationary
Container Size	35 lb (16kg)	120 lb (54kg)	400 lb (180kg)	400 lb (180kg)
Package Number	222077	226342	226269	224826*
Pump Only	206405	206699	206700	224825 (SST pump)
Dispense Kit	222079	222079	222082	224023
Tip	286517			286211 / 286621
Hose Length	15 ft (4.6m)	15 ft (4.6m)	25 ft (7.6m)	25 ft (7.6m)
Cover	222058	204574	200326	-
Caster Base	-	204144	-	-
Instruction Manual	307879/306531			308069

* Package (224826) includes flexible short tube (224022) long enough for 400 lb (180kg) container, but can be trimmed to accommodate smaller containers.