



BULLDOG 43:1 HYDRAULIC SUPPLY PUMP

Item code: GRACO-BULLDOG-43:1

The Bulldog 43:1 air-powered pump, with its efficient, large ported air valve, is the highest-performing in its class. Downtime is minimized by an air motor design that has been developed and tested for more than 10 million cycles of operation. Compact, durable, and reliable under tough working conditions. Ideal for blowout preventor systems.

FEATURES:

- Compact, low-profile design makes installation easier.
- Corrosion resistant – lightweight aluminum construction.
- Added safety – grounded lug prevents static build-up.

TECHNICAL SPECIFICATIONS:

- Maximum Operating Pressure: 4300 psi (301 bar).
- Maximum Air Input Pressure: 100 psi (7 bar).
- Air Inlet: 3/4 npsm(f).
- Fluid Inlet: 1 npt(f).
- Fluid Outlet: 3/4 npt(f).
- Wetted Parts: CS, SST, Chrome Plating, Zinc Plating, Nickel Plating, Brass, Buna-N.
- Instruction Manual: 307714.

ORDERING INFORMATION:

Code	Description
218334	43:1 Bulldog Hydraulic Supply Pump
Air Pressure Regulators	
206197	1/2 inch npt inlet and outlet
207755	3/4 inch npt inlet and outlet
Air Line Filters	
106149	1/2 inch npt inlet and outlet
106150	3/4 inch npt inlet and outlet
Grounding Clamp and Wire	
103538	Grounding clamp
222011	Ground wire

Code	Description
Bleed-Type Master Air Valve	
107142	1/2 inch npt inlet and outlet
Air Line Lubricator	
214848	1/2 inch npt inlet and outlet
214849	3/4 inch npt inlet and outlet
Repair Kits	
24U227	Pump lower repair kit
24U228	Air motor repair kit
24W515	Pump and air motor repair kit