



Pneumatic

HUSKY 2150 2" DIAPHRAGM PUMPS

The Husky 2150 has a 2 inch (50.8 mm) connection and is available in polypropylene, aluminum, SST and iron. The Husky 2150 air operated diaphragm pump features a stall-free low pulsation air valve which provides a smooth and rapid changeover.

FEATURES:

- Maximum Fluid Flow: 150 gpm (568 l/min)
- Maximum Fluid Discharge Pressure: 120 psi (8 bars, 0.8 MPa)
- Maximum Size Pumpable Solids: 1/4 inch (6.3 mm)
- Fluid Displacement Per Cycle: 1.03 g (3.9 litres)
- 2 inch (51 mm) ANSI end-porting.
- Fluid flow up to 150 gpm (568 lpm).
- Fluid pressure to 120 psi (8.4 bar, 0.84 MPa).
- Lube-free operation.
- Epoxy-coated air section for tough environmental conditions.
- Available in aluminum, 316 stainless steel, ductile iron and polypropylene.

BENEFITS:

- Overall improved efficiency (up to 40% more efficient).
- Highest fluid flow rate in its class.
- Up to 5 times longer diaphragm life compared to other air operated diaphragm pumps.
- Expanded material offering to handle endless applications.
- Fewer parts than industry peers, the complete air valve is externally accessible so it can be serviced fast and easy without removing the diaphragm pump.

SERIES OPTIONS:

Typical Application	Code	Airmotor	Manifolds	Seats	Balls	Diaphragms
Oil, Hot Oil, Unleaded Fuel, Coolant typical Lube application	DF3525	Aluminium	Aluminium NPT	TPE	Acetal	TPE
Oil, Hot Oil, Unleaded Fuel, Coolant typical Lube application	DFC525	Aluminium	Aluminium BSP	TPE	Acetal	TPE
Waste Oil, Diesel etc same as Buna good abrasion resistance	DF3GGG	Aluminium	Aluminium NPT	Geolast	Geolast	Geolast
Waste Oil, Diesel etc same as Buna good abrasion resistance	DFCGGG	Aluminium	Aluminium BSP	Geolast	Geolast	Geolast