



Pneumatic

HUSKY 716 3/4" DIAPHRAGM PUMPS

The Husky 716 air operated diaphragm pump delivers up to 16 gpm (60.6 lpm) of fluid and features center and end porting options. This 3/4-inch double diaphragm pump has an external controller for remote control capabilities and is available in aluminium and 316 stainless steel constructions. Ideal for bulk antifreeze and windshield solvent transfer.

FEATURES:

Max fluid flow:	16 gpm (61 l/min)
Max Fluid Discharge Pressure:	100 psi (7 bars, 0.7 MPa)
Max size pumpable solids:	3/32 in (2.5 mm)
Fluid displacement per cycle:	0.04 in (0,64 liter)
Max suction lift:	4.5 m dry, 7.6 m wet
(water with buna balls)	

BENEFITS:

- Center- and end-porting.
- No mechanical seals which causes fluid leaks or failures.
- Runs quietly at less than 85 dBa with easy-to-use remote muffler capability for even lower noise levels.
- Easy-to-service air valve and ball checks.
- 3/4 in (19.05 mm) center- and end-porting.
- No seals to leak or fail.
- Easy-to-service air valve and ball checks.

SERIES OPTIONS:

Typical Application	Code	Airmotor	Manifolds	Seats	Balls	Diaphragms
Oil, Waste Oil, Diesel, Coolant Typical Lube application. No ULP	D53277	Aluminium	Aluminium NPT	Acetal	Buna	Buna
Oil, Waste Oil, Diesel, Coolant Typical Lube application. No ULP	D5C277	Aluminium	Aluminium BSP	Acetal	Buna	Buna