



Pneumatic

FIRE-BALL 425 SERIES 50:1 GREASE PUMP

The Fire-Ball 425 features a large air motor to supply the power you need for long pipe runs and higher-volume dispensing. An ideal choice for applications where multiple dispenses happen at the same time. The Fire-Ball 425 is the pump of choice for your most demanding high volume applications.

FEATURES:

- Durable Casting - Thick cast aluminum air motor housing offers unmatched durability.
- Fewer Repairs - Fewer moving parts in the air motor assembly means less downtime and low repair cost.
- Superior Sealing - Non-metallic poppet valves offer positive sealing performance, even with contaminated "dirty" air environments for long life without repair.
- Extended Seal Life - In-line pump design aligns the air motor piston and fluid piston rods to maximize seal life.
- Corrosion-Resistant - Corrosion-resistant design utilizes liquid salt nitriding, nickel plating, stainless steel, aluminum and chrome on key components for longer life.

APPLICATIONS:

- Automotive dealerships
- Fast lube centers
- Fleet service facilities
- Heavy-duty dealerships
- In-plant
- Lube trucks
- Lubricant transfer
- Mining
- Service shops

SPECIFICATIONS & PERFORMANCE:

Annual Usage	Line Length	Simultaneous Dispense Points	Approx. Free Flow Rate @ 100psi	Air Inlet	Fluid Outlet	Air Operation Range	Description	Part Number
9,072 kg (> 20,000 lbs)	6 m (Up to 250 ft)	4 or more	4.1 kg/min (9 lbs/min)	1/2 in NPT(F)	3/8 in NPT(F)	40-150 psi (2.8-10.3 bar)	55 kg (120 lb) Grease Pump – 50:1	205394 – STK
							180 kg (400 lb) Grease Pump – 50:1	205395 – STK *306674

*Manual Number

STK – Stocked item in local warehouse

NSA – Non-stocked item that will be delivered to local warehouse by air freight

NSO – Non-stocked item that will be delivered to local warehouse by ocean freight