



Pneumatic

GT 750 36:1 UNIVERSAL GREASE TRANSFER PUMP

with bung adapter - NPT

The GT 750 pump was engineered to perform in challenging applications and changing environments. The large 7.5-inch (190 mm) air motor and pump lower combination allows the GT 750 pump to move the same amount of grease with up to four times fewer pump strokes.

FEATURES:

- Efficient Air Motor - Use less air to move more grease.
- High Flow Rates - Up to 32 lb/min (13.6 kg/min) of grease.
- High Volume Per Stroke - Pump more grease without having to drive pump too quickly to damage seals.
- Proven Pump Technology - Based on Graco NXT™ pump technology.
- Multiple Tank Options - Available in 35, 120 and 400 lb (16, 54 and 181 kg) down tube lengths.

APPLICATIONS:

- Fleet service facilities
- Heavy-duty dealerships
- In-plant
- Lube trucks
- Mining

SPECIFICATIONS & PERFORMANCE:

Annual Usage	Line Length	Simultaneous Dispense Points	Approx. Free Flow Rate @ 100psi	Air Inlet	Fluid Outlet	Air Operation Range	Description	Part Number
9,072 kg (> 20,000 lbs)	76 m (Up to 250 ft)	4 or more	14.5 kg/min (32 lbs/min)	1/2 in NPT(F)	1 in NPT(F)	40-100 psi (2.8-7 bar)	Universal Pump	24W498 – STK
							55 kg (121 lb)	25D116 – STK
							180 kg (400 lb)	24W337 – STK
								*3A5363

*Manual Number

STK – Stocked item in local warehouse

NSA – Non-stocked item that will be delivered to local warehouse by air freight

NSO – Non-stocked item that will be delivered to local warehouse by ocean freight