



15:1 FIRE BALL 300 GREASE PUMP RANGE

Item code: GRACO-300-15:1

Priming piston pump in combination with the appropriate feeding technology provides positive pump feeding, even with viscous and/or tacky greases. Designed to dispense medium pressure, low to medium volume grease, up to NLGI #0. Typically used by Automotive dealerships, Heavy-duty dealerships, Fast lube and service centers, Fleet service facilities, Lube trucks, Mining and In-plant.

FEATURES:

- Non-corrosive air motor design for long life.
- Double-acting pump ensures smooth fluid flow.
- Robust grease inlet cage withstands the most abusive handling.

SPECIFICATIONS:

Continuous-Duty Flow Rate:	0.7 gpm
Maximum Fluid Pressure:	2700 psi (186 bar)
Air Motor Effective Diameter:	3 in (7.6 cm)
Operating Range:	40-180 psi (2.8-12.5 bar)
Approximate Air Use:	17 cfm@ 100 psi (7 bar)
Wetted Materials:	CS, AL, Leather, PTFE, Rubber
Air Inlet Port Size:	3/8 in npt(f)
Material Inlet:	1 in npt(f) Straight Inlet
Material Outlet:	1/4 in npt(f)
Line Length \ddagger :	Up to 250 ft (76.2 m)
Dispense Points:	1 to 2
Annual Usage:	Up to 10,000 lb (4,535 kg)

PRODUCT RANGE:

Code	Description
Pump Range	
206405	35 lb (16 kg) Grease Pump - 15:1
206699	120 lb (55 kg) Grease Pump - 15:1
206700	400 lb (180 kg) Grease Pump - 15:1