

PETRO INDUSTRIAL



petroind.com



LDX HOSE REEL SERIES

Graco's industrial-grade LDX hose reel offers incredible value for cost-conscious workshops. Its all-metal frame and specially crafted, long-lasting components provide consistent release and retraction. Designed for smaller garages, independent repair facilities and industrial manufacturing environments.

FEATURES:

- Dual Pedestal Frame - Ribbed metal for increased stability and robustness.
- External Swivel Housing - Quickly access swivel seal for faster repairs.
- Ball Bearing Swivel - Swivel designed with internal ball bearings reduces friction and ensures smooth operation.
- Adjustable Arm - Easily change to one of six arm positions to fit your application.
- Large Hose Capacity with Small Profile - Compact design accommodates up to a 50 foot (15 meter) hose to meet a wide variety of application requirements.

FLUIDS:

- Petroleum- and synthetic-based oils
- Air
- Water
- Grease
- Antifreeze
- Windshield washer fluid
- Diesel exhaust fluid (DEF)

LDX SERIES OPTIONS:

Code	Fluid	Hose		Connection Size		Maximum Pressure PSI	Enclosed
		ID (in)	Length (ft)	Inlet (in)	Outlet (in)		
HEL010	Air/Water/Antifreeze/Windshield Washer Fluid	3/8	50 (15m)	3/8 NPT	3/8 NPT	300	No
HEL015	DEF	1/2	45 (14m)	1/2 NPT	1/2 NPT	150	No
HEM004	Oil	1/2	50 (15m)	1/2 NPT	1/2 NPT	1,500	No
HEH006	Grease	3/8	50 (15m)	3/8 NPT	3/8 NPT	4,060	No

Typical Application:

- Small maintenance shops
- Tire maintenance shops
- Small fast lubes
- Independent repair facilities
- Industrial manufacturing facilities

DIMENSIONS:

A	3.5 in (89mm)	E	19.0 in (483mm)
B	7.5 in (191mm)	F	9.4 in (239mm)
C	4.9 in (125mm)	G	17.5 in (445mm)
D	8.7 in (221mm)		

