



Diesel Exhaust Fluid

IN-LINE ELECTRONIC METER

Item code: GRACO-24G738

The in-line electronic meter is specifically designed to measure the quantity of Diesel Exhaust Fluid dispensed, and is suitable for indoor use only. Not approved to European explosive atmosphere requirements or for use in hazardous locations.

- Reset capable for periodic dispense history information.
- Shock-resistant durable design ideal for rugged environments.
- Easy-to-use meter dispenses pints, quarts, liters or gallons.

TECHNICAL DATA:

Flow range	0.5 to 15 gpm (1.9 to 57 lpm)
Maximum working pressure	1500 psi (10.3 MPa, 103 bar)
Minimum working pressure	5 psi (34 MPa, 0.3 bar)
Weight	1.8 lb (0.82 kg)
◆ Unit of measurement	Factory-set in quarts
♣ Accuracy	+/- 2.5% after calibration
♠ Repeatability	+/- 0.15%
Inlet and outlet	1/2 bspp
Operating temperature range	-4°F to 122°F (-25°C to 50°C)
Storage temperature range	-13°F to 122°F (-25°C to 50°C)
Wetted parts	SST, nickel, fluoroelastomer
*Batteries	2 AA Alkaline
Expected battery life	6 to 12 months

- ◆ Display shows quantity in 0.01 increments up to 999.99 gallons, quarts, pints or liters. Totalizes in gallons or liters up to 99,999 units.
- ♣ At 2.5 gpm (9.5 lpm) at 70°F (21°C), with water and 1 gallon dispensed. May require calibration; out-of-box accuracy is +/- 5%.
- ♠ At 2.5 gpm (9.5 lpm), at 70°F (21°C), with water and 1 gallon dispensed.
- * Recommended batteries: Duracell®, Energizer®, Eveready®, EN22®