



SDV15 CONTROL VALVES

For standard and heavy-duty applications, both indoor and outdoor, the SDV15 control valves are designed to perform in larger dealerships with longer plumbing runs and greater fluid usage. The control valve is compatible with a wide range of nozzles and fluid extensions and is capable of pumping oil up to 15 gpm (56.8 lpm).

Typical applications include Automotive dealerships, Heavy-duty dealerships, Fast lube centers, Fleet service facilities, Service shops, In-plant, Lube trucks, and Mining.

FEATURES:

- Lock-on/Lock-off trigger allows hands free operation
- Sturdy cast body designed for use in tough environments
- Inlet 1/2 in. NPT with swivel
- Features rigid extension with oil nozzle

SDV15 CONTROL VALVE RANGE:

Fluid	Max Working Pressure	Max Flow Rate	Intended Use	Extension	Inlet inch (mm)	Part Number
Oil	1,500 psi (103.4 bar)	15 gpm (56.8 lpm)	Indoor/Outdoor	Flex	1/2 (13) NPT	247713 – STK
				Rigid		247712 – STK
Anti-freeze				Flex		247713 – STK
				Rigid		247712 – NSA
Gear				Gear		247714 – NSA

ACCESSORIES

256164	Filter kit includes (10) filters/strainers (185416).
255459	Quick-close nozzle only for oil.
255460	Quick-close nozzle only for anti-freeze.
255470	Quick-close nozzle only for gear lube.
255461	Quick-close high-flow nozzle only for oil and anti-freeze.
255857	Non-drip quick-close high-flow nozzle with rigid extension for oil and anti-freeze.
255858	Non-drip quick-close high-flow nozzle with flexible extension for oil and anti-freeze.