

petroind.com



HOSE REEL LD SERIES ENCLOSED

FEATURES:

- Designed for light-duty applications.
- Enclosed for safety and protection, extends hose life.
- Flexible mounting options-hang on wall or ceiling; bench, table or tank top-mount options are available.
- Full-flow swivel maximises fluid flow with minimal pressure drop.
- Easy spring tension adjustment–increase or decrease pressure spring tension while reel is pressurised.
- Enclosed hose reel comes with ceiling/wall mounting swivel bracket.
- Required inlet hose kit sold separately.
- Reel Only No Mounting Hardware Included.

RAN	C =	ODT		IC.
nAN	GL	UFI	IUI	NЭ.

Code	Application	Hose Size & Lenght		Pressure psi (bar)	Connection Size Inlet NPT (m) x Outlet NPT (m)
24H655	Air	6mm x 11m	1/4" x 35ft	250 (17.2)	1/2" x 1/4"
24H655	Air	6mm x 15m	1/4" x 50ft	250 (17.2)	1/2" x 1/4"
24H655	Air & Water	10mm x 11m	3/8″ x 35ft	250 (17.2)	1/2" x 3/8"
24H655	Air & Water	10mm x 15m	3/8" x 50ft	250 (17.2)	1/2" x 3/8"
24H655	Air & Water	12mm x 11m	1/2″ x 35ft	250 (17.2)	1/2" x 1/2"
24H655	Air & Water	12mmx 14m	1/2" x 45ft	250 (17.2)	1/2" x 1/2"
24H655	Oil	10mm x 11m	3/8″ x 35ft	1800 (124)	1/2" x 3/8"
24H655	Oil	12mm x 11m	1/2″ x 35ft	1800 (124)	1/2" x 1/2"
24H655	Grease	6mm x 11m	1/4" x 35ft	5000 (345)	3/8" x 1/4"

SHIPPING DATA:

Weight (kg)	Dimensions (mm)		
11	650L x 180W x 470H		