

petroind.com



Self Bunded (Double Wall)

DIESEL/ADBLUE SPLIT COMPARTMENT STORAGE TANKS

FEATURES:

- Approved to AS1940, AS1692, AS1657.
- Adblue compartment 304 Stainless steel primary tank and 304 stainless steel wetted parts.
- Integrated Bunded Pump Bay and Tank Access Platform design providing access to the both compartments in one convenient location on the tank.
- Dispensing Equipment housed within a lockable bunded pump bay housing with container doors.
- Available in CSC plated standard container footprints.
- Diesel compartment = Fill Line 3" Overfill valve, 3" Fire Safe Ball Valve and Duo Check Valve / Suction Line 3" Anti-sphon Valve and 3" Fire Safe Ball Valve.
- Adblue compartment = Fill Line 2" Overfill valve, 2" Fire Safe Ball Valve and Duo Check Valve /Suction Line 2" Anti-sphon Valve and 2" Fire Safe Ball Valve.
- Overfill alarms in each compartment.
- 600mm manways with integrated tank access ladder assembly.

- AS1657 Designed and Approved Ladder and Platform Assembly for access to each tank compartment for dipping and ongoing tank maintenance.
- Full under tank visibility allows for regular visual inspect of the tank base and prevents the base rusting by providing for unrestricted air flow under the tank.
- Paint Colour RAL9003 Signal White/Tanks are sandblasted to SA2 Standard. Hempel Marine Paint 3 Stage process. Primer Hempadur 1530. 2nd Coat Hempadur Hi-Build 4520. Final Coat Hempathane Enamel 55100 Finished dry film thickness no less than 180 um.
- Supplied with all required statutory safety decals for your region of operation.







PRODUCT RANGE:							
Code	Capacity	Safe Fill Level	Length (m)	Width (m)	Height (m)	Weight (kg)	Container Footprint
LTAB30	D = 24,650L A = 4,740L	D = 23,415L A = 4,500L	6	2,4	2,9	8299	20FT High Cube
LTAB68	D = 59,665L A = 7,368L	D = 56,680L A = 7,000L	12	2,4	2,9	14104	40FT High Cube
LTAB110	D = 99,000L A = 11,000L	D = 90,000L A = 10,000L	14,4	3	3,2	20927	Breakbulk



LTAB Tank in Preparation and Customization



CERTIFICATIONS



Certificate of Compliance #20120912-MH49221 for UL 142, ULC-S601.



Decals manufactured to comply with AS1319 and AS2700.