



RETRACTA CW100 COLD WATER WASH SPRING REWIND HOSE REEL

Item code: CW2121

Cold water wash reel supplied with 15 m x 12.5 mm ID reinforced PVC hose. Operating pressure up to 1000 kPa (150 psi). 3/8" BSP (F) reel inlet, hose nozzle provided. Complete with carry handle and mounting bracket.

FEATURES:

- Positive latching mechanism allows mounting in any position.
- Made from weather resistant, high impact UV stabilised polypropylene.
- Low rewind tension allows easy hose pull out.
- full stainless steel mouth for improved hose and reel service life.
- BU100 lockable wall or overhead mounting bracket enables 180° rotation.
- Reel casing available in various colours (conditions apply)
- Fully serviceable.
- 10 year warranty and parts guarantee.
- Accessory – Bench Bracket. Code: BB100

RANGE OPTIONS:

Code	Description	Hose		Working pressure	Hose material	Colour		Max. working pressure	Reel inlet (BSP/NPT)	Hose outlet (BSP/NPT)
		ID (mm)	Length			Reel	Hose			
AW100 / AW2101	Compressed air / water	10	20m	1 700 kPa (250 psi)	Reinforced PVC	Blue	Blue	60°C	3/8"	1/4"
AW150 / AW2150	Compressed air / water		15m							1/4"
AW200 / AW2121	Compressed air / water	12.5		1 000 kPa (150 psi)		White	Hose nozzle			
CW100 / CW2121	Cold wash									
DR100 / DR2121	Garden water	12.5	18m	860 kPa (125 psi)	Green	Green	90°C	3/8"	3/8"	
HW100 / HW2121	Hot water		12m	1 400 kPa (200 psi)	Reinforced rubber	Red				Red
HWP100* / HWP2101	High pressure hot water	10	12m	20 700 kPa (3000 psi)	Reinforced rubber (SAE 100 R2AT)	Red	Black	95°C	3/8"	
PW100 / PW2121	Potable water	12.5	15m	1 000 kPa (150 psi)	Reinforced LDPE	Blue	Blue	60°C		