

TCS 682 METER SERIES

The 682 series piston flow meter is a true positive displacement flow meter that has an inline design consisting of three (3) reciprocating pistons operating within their respective measuring chambers, where each piston works in a manner similar to an automobile engine.

The pistons are fitted to a wobble plate, which has a shaft extending from its upper surface and a valve pivot attached beneath it. The valve pivot drives a sliding valve from piston to piston as a known amount of product flows through each cylinder bore, controlling the sequence of events in a smooth mechanical motion.

SPECIFICATIONS:

Design: reciprocating three (3) piston. **Size:** 40nb (1 1/2") flange connection.

Type: SP, SPA, SPD, AF and SS.

Flow range: 0.2 to 50 GPM (0.76 to 190 LPM).

Linear accuracy capable of: +/- 0.1% over flow range.

Repeatability: 0.01% over 250:1 turndown.

Pressure: 150 PSI (10.5 BAR).

Temperature: - 40 to 160°F (- 40 to 71°C).

Material: Aluminum, Ductile iron and Stainless Steel.


Seals: Viton®, Teflon® and Simriz®.


FEATURES:

- Superior accuracy over the entire flow range.
- Low maintenance.
- · Long service life.
- 75 years of proven performance and acceptance.
- Wide viscosity range up to 50,000 SSU (11,000 CPS).
- Meets NIST, NMI, OIML, SABS and many other international weights and measures certifications.
- Industry leading 10 year warranty.









METER TYPES & FLUIDS COMPATIBILITY:

- SP = Standard Petroleum: Gasoline, Fuel Oils, Diesel, Bio-Diesel, Kerosene, Vegetable oils, Motor Oils, Ethylene Glycol, Naptha etc.
- SPA = Standard Petroleum Aviation: Aviation Gasoline, Gasoline, Jet Fuels, Fuel Oils, Diesel, Bio-Diesel, Kerosene, Naptha, etc.
- SPD = Standard Petroleum Ductile (Nodular) Iron: Ethanol, Methanol, Aviation Gasoline, Gasoline, Diesel, Bio-Diesel, Fuel Oils, Kerosene, Vegetable Oils, Motor Oils, Naptha, etc.
- AF = All Ferrous: Industrial Chemicals, Solvents, Pesticides, Nitrogen Solutions, Fertilizer, Chlorinated Solvents, Paints, Inks, Alcohols, Adhesives, Molasses, Corn Syrup etc.
- SS = Stainless Steel: Industrial Chemicals, Solvents, Nitric Acid, Phosphorus Acid, Glacial Acetic Acid, Anti-Icing Fluid, Vinegar, Fruit Juices, etc.

PETRO Contact Information

AFRICA

South Africa

Factory 14 Bentonite Street Alrode, Alberton, Johannesburg South Africa P: +27 (0)11 864 7758 F: +27 (0) 11 864 1649 E: sales@petroindustrial.co.za

UAE

Dubai

Office LB17330, Lobby Building 17
Jebel Ali Free Zone
PO Box 18602
Dubai, United Arab Emirates
P: +971 488 76688
F: +971 488 76932
E: salesuae@petroind.com

AUSTRALIA

Eastern Australia

Factory 2, 106 Potassium Street PO Box 407 Narangba QLD 4504 P: 07 3204 9558 F: 07 3293 4852 E: sales@petroindustrial.com.au

Western Australia

173 Mulgul Road, Malaga WA 6090 AU P: +61 (8) 6305 0855 E: saleswa@petroperth.com.au



petroind.com