



ELECTRONIC OIL CONTROL GUN 30LPM - PRESET

Item code: HG60-01

FEATURES:

- 5-digit resettable batch totaliser (19999).
- 6-digit accumulative totaliser.
- 5 variable preset totals available for use.
- Sleep mode (2 minutes idle limit) to preserve battery life.
- EEPROM retention allows all information to be retained if batteries are removed.
- Oval gear mechanism for optimum accuracy.
- Automatic non-drip nozzle.
- 2 outlet nozzle positions (in-line or 90 degrees).
- Rigid extension.
- Simple handle latch design.
- Shock resistant.
- Fully serviceable.
- 10 year warranty and parts guarantee.

SPECIFICATIONS:

- **Compatible fluids:** engine oil, diesel oil, automatic transmission fluid and anti-freeze/anti-boil, with a maximum viscosity of SAE 140.
- **Wetted components:** aluminium, acetal, steel, nitrile rubber.
- **Accuracy:** $\pm 0.5\%$ of reading (lubricating oils).
- **Flow range:** 1-30 L/min (0.26 – 8 US gal/min).
- **Max. pressure:** 10 350 kPa (1 500 psi, 103.5 bar).
- **Pressure loss:** 100 kPa (14.4 psi, 1 bar) @ 12 L/min (3.2 US gal/min) (without nozzle) with calibration fluid.
- **Weight:** 1.16 kg (2.55 lbs).
- **Swivel inlet:** ½" BSP or NPT.
- **Operating temp:** 0°C (32°F) to 50°C (122°F).
- **Storage temp:** -10°C (14°F) to 60°C (140° F).
- **Battery:** 2 x 1.5 volt alkaline AA.

ACCESSORIES:

Code	Description
HGFEX	Flexible Extension
H6	Range Coloured Shrouds
HGFM	Flexible Metal Extension