



## P6001 BARE REPLACEMENT PUMP UNIT

Item code: P6001

**NOTE:** Replacement Pump Unit Only.

50:1 air operated MAXILUBE® for 50 to 55kg drums. B2 'Booster Gun' provides boost pressure up to 68 900 kPa (10,000 psi). Complete with 4m hose. Suitable for underground coal mine applications.

The P6 MAXILUBE® offers the same features & benefits as the P3 POWERLUBE®, but has models available to suit grease containers from 50kg (110lbs) to 55kg (120lbs).

### FEATURES:

- Quiet, non-corroding air motor.
- Low air consumption.
- No air line lubricator required.
- Rubber edged follower plate.
- 4m (13 ft.) x 6 mm (¼") ID delivery hose.
- B2 booster gun with 360° ZSB swivel.
- Fully serviceable.
- 10 year warranty and parts guarantee.

### SPECIFICATIONS:

- Grease viscosity: up to NLGI No.2
- Wetted components: zinc and hard chrome plated carbon steel, brass, and nitrile and polyurethane rubber
- Output: approx. 460 g/min (16 oz/min)
- Max. air pressure: 1 030 kPa (150 psi, 10.3 bar)
- Min. air pressure: 400 kPa (60 psi, 4 bar)
- Min. compressor size: 0.08 m<sup>3</sup>/min (3 cfm)
- Air inlet/fluid outlet: ¼" NPT (F)
- Pump ratio: 50:1 (grease pressure is 50 times air pressure)
- B2 gun pressure: up to 69 000 kPa (10 000 psi, 690 bar)
- Hose thread: ¼" NPT (M)

### ACCESSORIES:

- TR6 – Trolley
- PDF13 – Push On Extension
- PDF21 – Push On Extension
- TA-7K – Filter & Regulator Kit
- KZDXL – Straight Needlepoint Coupler
- KRV – Pressure Release Valve