

macnaught

BARE REPLACEMENT PUMP UNIT

Item code: P8-01

NOTE: Bare replacement pump only.

The P8 MAXILUBE® is a larger version of the P6, designed to fit 180 kg (400 lbs) grease containers. The P8 MAXILUBE is also suitable for underground coal mine applications.

FEATURES - P8-01 PUMP ONLY:

- Quiet, non-corroding air motor.
- Low air consumption.
- No air line lubricator required.

FEATURES - P8-11 COMPLETE SYSTEM:

- Drum lid.
- Rubber edged follower plate with built-in release. valve and removal system.
- 2.5 m (8 ft.) x 6 mm (1/4") ID delivery hose.
- B2 booster gun with 360° ZSB swivel.
- Fully serviceable.
- 10 year warranty and parts guarantee.

SPECIFICATIONS:

- Grease viscosity:
 - up to NLGI No.2.
 - Wetted components: zinc and hard chrome plated carbon steel, brass, and nitrile and polyurethane rubber. approx. 460 g/min (16 oz/min).
- Output: .

•

- Min. air pressure: 400 kPa (60 psi, 4 bar).
- Min. compressor size: $0.08 \text{ m}^3/\text{min}$ (3 cfm). 1⁄4″ NPT (F).
- Air inlet:
- Pump outlet: 1/4" NPT (F).pump ratio: 50:1 (grease pressure is 50 times air pressure).
- B2 gun pressure: up to 69 000 kPa (10 000 psi, 690 bar).
- Hose thread: 1/4" NPT (M) greasing equipment - air operated.

ACCESSORIES:

- PDF21 Push On Extension
- ACK2 Aviation Kit

- MCFK1 All-purpose Air Greasing Kit
- TR205 Trolley