



**M** MORRISON BROS. CO.

## FUSIBLE GLOBE VALVE SERIES 939

Item code: MORRISON-FGV

Fusible globe/gate valve are used to shut off product flow in the event of fire.

**WARNING:** 939 Series valves require periodic inspection to ensure the shutoff mechanism is operating. Should not be opened under pressure.

### FEATURES:

- Fusible element integrated into the hand-wheel melts at 165°F causing the valve to close.
  - Recommended use with fuel oil and kerosene service.
  - 10 PSI maximum operating pressure 1/4" to 3/4" sizes.
  - 25 PSI maximum operating pressure 1" size.
  - Not intended for use as a block valve, intended as a normally open valve.
  - 1/4", 3/8", and 1/2" are UL and ULC listed.
- Construction Details:
- Body, bonnet, and stem: Brass

### RANGE OPTIONS:

Code	Size	Description	Weight
93900501V	0.25"	Fusible Globe Valve, Brass, With 165 Degree Fuse	0.5
93901001V	3/8"	Fusible Globe Valve, Brass, With 165 Degree Fuse	0.5
93902001V	0.5"	Fusible Globe Valve, Brass, With 165 Degree Fuse	0.75
93903001V	0.75"	Fusible Globe Valve, Brass, With 165 Degree Fuse	1
93904001V	1"	Fusible Globe Valve, Brass, With 165 Degree Fuse	2.25