



petroind.com



110% Self Bunded

# **BAFFLED PC CUBE SERIES**

Suitable for the storage and dispensing of Diesel, Biodiesel, Kerosene, Lubricants, Petrol and Waste Oil.









The PC Cube is a market leading self bunded tank, with versatile under-hatch connections and an intelligent design certified for lifting when full (Up to PC6.6).

#### **FEATURES:**

- Unique tank in tank design approved to UL142 / ULCS601 / AS1940, AS1692, AS1170, AS4100, AS1554.1 / BS799 / PPG2.
- Certified Crane Lifting Points (Up to and including PC6.6)
- Removable manway for ease of maintenance.
- The outer tank will hold 110% of the inner tank's capacity.
- UN31A/Y approved for the transport of Dangerous Goods by Road, Rail and Sea, Packaging Groups II & III. (PC0.66 - PC2.25)
- Lockable hatch lid with access for hoses, under hatch sockets and suction spears can operate with the hatch
- Additional 50mm (2") hose entry and exit sockets on top of tank.
- Secure under-hatch generator hose suction and return points, to accommodate up to 3 generators.
- 4 x way forklift pockets.
- Incremental dipstick.
- Stackable 3-high empty and 2-high when full.
- Supplied with all required statutory decals.
- Movable when full



We are proud to announce that PETRO Industrial has passed all of the audits and scrutiny applied by SAI Global, leading to the certification of our Quality Systems and Processes to ISO9001:2015.

View online at: www.petroind.com







petroind.com

## PRODUCT RANGE:

Please see the range of PETRO PC Cube Self Bunded Tanks below:

Code	Gross Volume (L)	Safe Fill Level (L)	External Dimensions (L x W x H) (mm)	Tare Weight (kg)
PC 0.66	660	600	1374 × 1086 × 810	451
PC 1.1	1100	1000	1374 x 1086 x 1270	594
PC 2.25	2250	2000	2294 x 1086 x 1270	885
PC 3.3	3300	3000	2294 x 1546 x 1270	1096
PC 4.5	4500	4000	2294 x 2084 x 1270	1328
PC 6.6	6600	6000	2966 x 2294 x 1270	1809
PC 8.8	8800	8000	3916 x 2294 x 1270	2170
PC 11	11000	10000	4876 x 2294 x 1270	2689

### **COMES WITH:**

- 1 x 25mm (1") Suction Spear
- 2 x 13mm (1/2") Suction Spear
- 3 x 40mm (1 1/2") Return Point
- 1 x Spare 80mm (3") Socket
- 4 x Spare 50mm (2") Socket Top of Tank
- 50mm (2") Fill Point Splash Fill Only
- Incremented Dip Stick (Select Models)

- Statutory Signage
- 4 Way Forklift Pockets
- Certified Lift Full Crane Lugs on Each Corner (Up to and including PC6.6)
- Finish Painted PETRO White Marine Specification





petroind.com

#### **CERTIFICATIONS**




Certificate of Compliance #20121129-MH49493 for UL 142, ULC-S601, and ULC-S653.



WS010 Proof Load Test Certificate Nata v2.2. #1,548. Accreditation No. 17109. Accredited for Compliance with ISO/IEC 17025.



Decals manufactured to comply with AS1319 and AS2700.



Internal Piping Dimensions Compliance Review Final Report. AS1962 and AS1940.



Cube Range AS1692 and AS1940 Compliance Verification.