



## 316 STAINLESS STEEL SPRING CHECK VALVE

Item code: SCV-CATA

316 Stainless Steel Full Port Spring Loaded Check Valve, 800 WOG c/w PTFE Seat.

### FEATURES:

- Soft PTFE seat for bubble tight shutoff, spring loaded for fast seating action.
- Low cracking pressure, 0.5 psi.
- Flow profile designed to minimize head loss.
- Perfect seating both at high and low pressure, wide temperature range: +10° to 450° F.
- Corrosion resistant—excellent for use on chemicals.
- ASTM-A351-CF8M investment casting.
- Connection: FBSP x FBSP.
- 125WSP saturated steam.
- ANSI B1.20.1 threads.
- Dual guided stem & disc.
- Size Range:
  - 8mm (1/4")
  - 10mm (3/8")
  - 15mm (1/2")
  - 20mm (3/4")
  - 25mm (1")
  - 32mm (1 1/4")
  - 40mm (1 1/2")
  - 50mm (2")

# PETRO Contact Information

## AFRICA

### South Africa

Factory 14 Bentonite Street  
Alrode, Alberton, Johannesburg  
South Africa  
P: +27 (0)11 864 7758  
F: +27 (0) 11 864 1649  
E: sales@petroindustrial.co.za

## UAE

### Dubai

Office LB17330, Lobby Building 17  
Jebel Ali Free Zone  
PO Box 18602  
Dubai, United Arab Emirates  
P: +971 488 76688  
F: +971 488 76932  
E: salesuae@petroind.com

## AUSTRALIA

### Eastern Australia

Factory 2, 106 Potassium Street  
PO Box 407  
Narangba QLD 4504  
P: 07 3204 9558  
F: 07 3293 4852  
E: sales@petroindustrial.com.au

### Western Australia

173 Mulgul Road, Malaga WA 6090 AU  
P: +61 (8) 6305 0855  
E: saleswa@petroperth.com.au

# PETRO INDUSTRIAL



[petroind.com](http://petroind.com)